



The LED strip is available in either warm or natural white strip is provided in either 1M, 2M or 3M lengths with a 2m soldered cable.

There is a VHB (very high bond) adhesive attached to the strip. The strip features cut marks every 50mm and has an IP65 rating.


1M-SY8983WW or NW 2M-SY8984WW or NW 3M-SY8985WW or NW

- 4W/m
- IP65
- 60 LED's per metre
- 50mm cut points
- 1.5m cable on one end

Suitable Power Converters		
SY9739A/MF	15W/12Vdc	Runs up to 3M
SY7350A/MF	20W/12Vdc	Runs up to 5M
SY7715	30W/12Vdc	Runs up to 7M
SY7351/50W	50W/12Vdc	Runs up to 12M

Compatible Accessories	
Kinetic Wireless Smart Controls (Including Dimming)	
Sensors Switches & Dimmers	
WiFi 4 Zone Controls (Including Dimming)	
2m (SY7183) or 5m (SY7183/5) Extension Cables	

Technical Information		
Power Supply	12Vdc	
Adhesive	VHB	
Cable Length	1.5m cable on one end	
Guarantee	3 years	
Colour Appearance	Warm White or Natural White	
Colour Temperature	3000°K—3500°K or 4000°K— 4500°K	
Colour Rendering Index	WW—Ra 85 NW— Ra 85	
Wattage	4W/m	
IP Rating	IP65	
Cut Marks	Every 50mm	
LED's per metre	60	





T: +44 (0) 113 286 6686







