


## **FEATURES**

The Sirius Connect features an innovative new plug and play system, in which the cable detaches directly from the back of the light unit enabling the fitting to be installed easily into the base of a cabinet. The Sirius Connect also features a diffused cover, so there are no visible LED points in the fitting, and also has a 120 degree beam angle which fills cabinets or work surfaces, eliminating dark spots.



$\in$	ROHS	N W	

THE TECHNICAL SPEC				
Fitting Type	LED			
Voltage	12vdc			
Colour Temperature	Natural White (4127k)			
Lamp Life*	30,000 hours			
Wattage	2.6W			
Number of LED's	6			
Luminous efficacy	Warm White—65 Natural White—70			
CRI	Warm White— 82 Natural White—85			
Cable Length	2m			
Mounting	Surface			
Beam Angle	120 Degree			
IP Rating	IP44			

\*Based

Part Numbers	Description	
SY9570WW or NW	Sirius Connect Recti light Stainless Steel—warm or natural white	SS
Suitable Power Converter		
SY9980B or SY9980A/MF***	12Vdc 8W LED Power Converter (1—3 lights)	
SY9739A/MF***	12Vdc 15W LED Power Converter (1—5 lights)	

<sup>\*\*\*</sup>Power converters with suffix A/MF are compatible with the Infinity connection system, please contact our office for further information









