IP68 FLEXILE LED STRIP










The clever design of the new Flexile LED strip allows it to bend tight curves whilst offering illumination to both vertical and horizontal planes, perfect for illuminating curved units or islands. The strip offers a solid colour with no visible LED points, and has an IP68 rating.

An accessory kit is available which includes mounting clips, screws and two end caps. the strip can be cut every 20mm, end caps must be applied to the cut end to maintain the IP rating of the product. 1.5m cables are coupled to both ends of the strip with pre-wired Molex connectors for use with the Sycamore range of 12vdc LED power converters.

THE TECHNICAL SPEC	
Fitting Type	LED
Voltage	12Vdc
Colour Temperature	3000K 4000k & 5000K
Wattage	10w Per Metre
IP Rating	IP68
Cut Marks	Every 20mm
LED Type	3014





Part Numbers	Description
SY8931WW/NW/CW	(Kit includes 3M of LED strip with 1.5M distributor cable at both ends, a 50W 12Vdc LED Power Converter (max 5m), and an accessory pack.)
SY8913	3M Flexile LED Strip Warm White
SY8914	3M Flexile LED Strip Natural White
SY8915	3M Flexile LED Strip Cool White
SY8930	Accessory pack (9 clips & 2 ends)
Suitable Power Converters	
SY7715	12vDC/30W LED Power Converter (Max 3m)
SY7351/50W	12vDC/50W LED Power Converter (Max 5m)
SY7440A	12vDC/100W LED Power Converter (Max 10m)









