


Dimensions shown are in mm

FEATURES

The new Sirius Range is at the forefront of modern technology, offering an ideal alternative to halogen lights. Designed to offer a superior light output, the Sirius has a diffused cover to mimic the appearance of halogen cabinet lights, and has no visible LED points. The panel is only 6mm thick, and is the first flat panel cabinet light in the U.K KBB market. The fitting is available in a brushed nickel finish.

Available in warm or natural white.



| | | _ |
|-------|--------|---|
| \in | ROHS W | |

| The Technical Spec | |
|--------------------|------------------------------------|
| Fitting Type | LED |
| Voltage | 12vdc |
| Colour Temperature | 3000k or 4000k |
| Lamp Life** | 30,000 hours |
| Wattage | 6W |
| Lumens Per Watt | (3000k) 37 lm/w (4000k) 43 lm/w |
| CRI | (3000k) Ra 81 (4000k) Ra 83 |
| Cable Length | 1.5m |
| Luminous Flux | (3000k) 172 lm (4000k) 249 lm |
| Mounting | Surface |
| Beam Angle | 110 Degree |
| IP Rating | IP20 |

^{**}Based on 70% of initial lumen output

| Part Numbers | Description | |
|-------------------------|--|--|
| SY7543BN SY7543BN/WW | Sirius 6W LED flat panel cabinet Light brushed nickel finish/natural white LED Sirius 6W LED flat panel cabinet light brushed nickel finish/warm white LED | |
| Suitable Power Conver | ters | |
| SY9739A/MF*** | 12Vdc 15W LED Power Converter (1—2 lights) | |
| SY7350A/MF*** | 12Vdc 20W LED Power Converter (1—3 lights) | |
| SY7351A | 12Vdc 48W LED Power Converter (1—6 lights) | |

^{***}Power converters with suffix A/MF are compatible with the Infinity connection system, please contact our office for further information









