





- Switch from Warm, Natural or Cool White (Triglow distribution block required)
- SOB Technology (SMD On Board) - Provides a higher luminous efficacy than COB LED strips.
- Perfect for applications where maximum output with lower energy consumption is critical
- Cut marks every 28mm, and any cut pieces can be re-used with the addition of our reconnection cable
- 2m cable on both ends
- 5 Year Guarantee



Part Code	Description	Voltage	Wattage Per Metre	Kelvins	LED's Per Metre	Lumens Per Watt	Cut Marks	Cable Length
SY2463-3	Lunox Triglow 3m Reel	24Vdc	6W	2700K/4000K/6000K	288	90 - 100lm	28mm	2m at both ends
SY2463-5	Lunox Triglow 5m Reel	24Vdc	6W	2700K/4000K/6000K	288	90 - 100lm	28mm	2m at both ends

Accessories

Part Code	Description
(a) SY5001	Triglow Distribution Block (Dimmable)
(b) SY2459/2M	2m Reconnection Distribution Cable
(c) SY2459C	30mm Corner Connector
(d) SY2459S	Direct Connector



LED Drivers

Part Code	Description
SY2499-I5	15W 24Vdc LED Driver (max 2.5m)
SY2499-30	30W 24Vdc LED Driver (max 5m)
SY2499-60	60W 24Vdc LED Driver (max 10m)

