




The clever and innovative design of the FLEXile LED strip allows it to bend around tight curves (minimum bend radius of 45mm) whilst offering illumination to both vertical and horizontal planes, which is a perfect solution for illuminating curved units or islands. The strip offers a solid colour with no visible LED points, and has an IP44 rating.



Technical Information	
Power Supply	12Vdc
Adhesive	N/A
Cable Length	1.5m at both ends
Guarantee	3 Years
Colour Appearance	Warm White, Natural White or Cool White
Colour Temperature	3000°K-3500°K, 4000°K-4500°K or 6000°K-6500°K
Colour Rendering Index	WW—Ra 84, NW—Ra 87, CW—Ra 87
Wattage	10W/m
IP Rating	IP44
Cut Marks	Every 20mm
LED's per metre	140

Part Numbers	Description
SY8931AWW/NW/CW	(Kit includes 3M of LED strip with 1.5M distributor cable at both ends, a 50W 12Vdc LED Power Converter (max 5m), and an accessory pack.)
SY8913A	3M Flexile LED Strip—Warm White
SY8914A	3M Flexile LED Strip—Natural White
SY8915A	3M Flexile LED Strip—Cool White
SY8930	Accessory pack (9 clips, 9 screws & 2 end caps)
Suitable Power Converters	
SY7530A/MF	20W 12Vdc LED Power Converter (Max 2m)
SY7715	30W 12Vdc LED Power Converter (Max 3m)
SY7351/50W	50W 12Vdc LED Power Converter (Max 5m)
SY7440A	100W 12Vdc LED Power Converter (Max 10m)