## D.com \_\_\_\_\_



This LED strip uncoated 5m reel of LED strip is available in either warm or natural white strip is provided in a 5m reel with a 2m distributor cable attached to each end. This allows a fast fit connection to the Sycamore range.

This offers a labour cost saving due to the time saved in connecting the strip to the driver. either end, which enables users to use the remaining strip once it has been cut.

There is a VHB (very high bond) adhesive attached to the strip. The strip features cut marks every 50mm and has an IP20 rating.

## SY8982 WW or NW-5m Reel

- 4W/m •
- IP20

- 60 LED's per metre •
- 50mm cut points
- 2m cable on both ends

Suitable Power Converters			
SY9739A/MF	15W/12Vdc	Runs up to 3M	
SY7350A/MF	20W/12Vdc	Runs up to 5M	
SY7715	30W/12Vdc	Runs up to 7M	


Compatible Accessories		
Kinetic Wireless Smart Controls (Including Dimming)		
Sensors Switches & Dimmers		
WiFi 4 Zone Controls (Including Dimming)		
Reconnection Cable (SY8977A)		
Reconnection Corner (SY8978A)		
2m (SY7183) or 5m (SY7183/5) Extension Cables		

Technical Information		
Power Supply	12Vdc	
Adhesive	VHB	
Cable Length	2m on both ends	
Guarantee	3 Years	
Colour Appearance	Warm White or Natural White	
Colour Temperature	3000°K-3500°K or 4000°K- 4500°K	
Colour Rendering Index	WW—Ra 80, NW—Ra 83	
Wattage	4W/m	
IP Rating	IP20	
Cut Marks	Every 50mm	
LED's per metre	60	

8mm (w)













W: www.sycamoreled.com

ISO 900 REGISTERE