# Sycamore LED.com

# Installation instructions : Sirius LED Plinth Lights SY7295

Thank you for purchasing this SycamoreLED.com product. Please make sure instructions are followed carefully prior to and during installation and product is not altered, otherwise warranty may not be valid. For technical support or warranty information please visit www.sycamoreLED.com, or call our dedicated technical helpline +44 (0) 113 2866686.

# IMPORTANT—Please read prior to installation

- 1) Please read these instructions carefully before commencing any work
- 2) Please retain these instructions for future reference
- 3) It is strongly recommended that this unit is installed by a qualified electrician in accordance with the IEE wiring regulations and building regulations
- 4) To prevent electrocution switch the power off at the mains supply before installing or maintaining this fitting
- 5) Ensure others cannot restore the electrical supply without your knowledge
- 6) The PSU must be rated 12VDC and be compatible with the pre-wired connector system of this product
- 7) Never exceed the wattage stated

### GENERAL

Item	Rated voltage/V	Rated power/W	LED numbers	IP Rating	Protection
SY7295	12v DC	4×1W	4	44	CLASS III

# PRE-INSTALLATION

- 1) Prepare all the parts and tools required for the installation
- 2) Turn off power before installation.
- 3) If the housing or glass diffuser is broken or damaged do not use it.

# INSTALLATION

- 1) For recessed cut a 28mm diameter hole on the surface to which the light is being installed (without the surface spacer part).
- 2) Put the wire through the hole
- 3) Connect the power with 12VDC driver & push the fitting into the hole.
- 4) Ensure the body of the lamp is securely fixed on the face of installation, then restore the power and check operation.
- 5) For surface mounting or to install within a wall, use the supplied surface spacer and follow instructions 2-4 above.

# CARE IN USE

CE 🕼 🕝 🔂 ROHS 🕱 🕅

- 1) Please note this fitting has non replaceable parts
- 2) Always switch off or disconnect from the mains when cleaning the product.
- 3) We recommend cleaning with a soft dry cloth. Do not use scourers, abrasives or chemical cleaners.

