

SYCAM Com



KITCHEN LIGHTING

2022/2023





To inspire our customers with innovative state of the art energy efficient lighting solutions

Sycamore Lighting has been at the forefront of lighting innovation since 1998. Our dedication to quality has resulted in sustained growth by offering a diverse range of lighting and the very latest in technology. Major investment in new technologies and personnel, together with state of the art testing and training facilities has enabled us to cross over into different market sectors, whilst also retaining our reputation as a major supplier of lighting and control systems to the KBB markets throughout the UK and Europe.

N OUR VALUES

To remain committed to building on our reputation of excellence in customer service and to continue implementing the latest energy saving technology into our products

ABOUT US

We undertake market research on a continuous basis, and listen to feedback from our customers. We welcome any suggestions as to what our clients would like to see added to our product collection. We use a number of reliable, ethical and professional suppliers, the majority of which we have been dealing with for over ten years.

We have a vigorous quality control system in place, with dedicated and qualified staff who ensure the quality of every new product, and batches thereafter are of consistent high quality.

As part of our dedication to quality control and product advancements, all our products are fully tested in our in house laboratory by our own qualified technical team to ensure they meet current regulations. Our huge warehouse facilities and constant stock control enable us to offer a quick and comprehensive delivery service.



Fnabl FD

LEDs and LED controls are the future of lighting, and as LED capabilities continue to evolve and expand, new markets are opening up all the time.



Developing new, innovative solutions for tomorrow's new LED applications takes significant investment in research and design, so by joining the EnabLED licensing program, Sycamore LED has gained access to over 490 Signify inventions and patented technologies, which we can now build into our own products. With access to these cutting-edge technologies, we can gain greater freedom to design optimal solutions for our products. We can shorten our time to market and also achieve an excellent balance of cost-to-quality including cost-effectiveness in our component sourcing.

Please visit www.signify.com/enabled to confirm which companies are currently licensed in the scheme and what the EnabLED licensing program covers in more detail.



ABOUT US

SUSTAINABILITY MATTERS

At Sycamore Lighting, we understand the need for sustainable products and practices to meet the needs of our current customers & stakeholders, without compromising the ability of future generations to meet their own needs. To see our full Sustainability matters promise please visit our website.

ISO 9001

We are proud to have achieved an ISO 9001 certification.

The quality management certification helps us to demonstrate the level of quality that we offer with our services, whilst also driving down costs, boosting productivity and improving customer satisfaction. With this certification we are aiming to cut costs by as much as 50%, reducing wasted resources through improved processes and efficiency.

Not only does ISO 9001 help to improve internal processes and efficiency, but it is an internationally recognised standard of quality.



We have been a member of the LIA since 2013, and to achieve membership with the LIA we have to consistently demonstrate the highest degree of professionalism, expertise and ethical standards in every aspect of our operations, including the safety, reliability, quality and support of our products and the competence of their employees and representatives. All our products are UKCA & CE marked as required to confirm that it complies with UK & EU law and that is 'fit for purpose' and safe. We also ensure that the products we offer for sale in the EU are supplied, manufactured or manufactured under licence to conform to any statutory requirements and standards as may be mandated by local law. We can also demonstrate the published features of any product that we supply and substantiate any benchmarks, performance characteristics, service ability levels or other criteria to which it lays claim.

THE KBSA

We are also corporate members of the KBSA. We are dedicated to upholding the Association's high standards of design, supply, and customer service throughout the KBB industry. As KBSA members we follow an Approved Code of Practice and are subject to strict monitoring to make sure our customers get the best professional service available.









OUR PRODUCTS ARE LISTED ON THE FOLLOWING PLATFORMS









OUR TECHNICAL TEAM

Looking for some assistance with any of your projects? Our technical and design experts are here to help, just follow the three simple steps below



Send your plan along with a short brief to tech@sycamoreLED.com

Our experts design the perfect lighting scheme for your project

You receive a quotation including a full list of products ready to order

BESPOKE LIGHTING SERVICE

We also offer a bespoke lighting service. For further details please see page 65, or call our technical team above to see how we can help.



ALL PRODUCTS ARE COVERED BY A 5-YEAR WARRANTY

Excludes battery operated products, accessories, pendants, power converters & motorised pop ups

OUR TESTING LABORATORY

Lighting has become a very technical subject, and as market leaders in our field, we have invested in a fully operational laboratory and employed a qualified electronics expert. This enables us to offer consistency of information for all the lighting products within our range, offering accurate data for lighting planners.

SPECTRORADIOMETER & INTEGRATING SPHERE

This apparatus has been installed within our laboratory to measure the photometric parameters of light fittings and lamps. We can offer accurate data in relation to lumen output, colour rendition, colour temperature and power factor of any given luminaires.

EMC TEST CABINET

Allied to the sphere, this piece of equipment measures the electromagnetic interference of light fittings and power converters under test conditions. This test enables us to determine the suitability of installations in different environments, and ensures that our range complies with the criteria that limits these types of emissions from electrical components.

GONIO-SPECTRORADIOMETER

The Gonio-Spectroradiometer tests light sources for photometric, colorimetric and electrical parameters. The test system can measure the luminous flux, luminous intensity, average beam angle and illuminance of the luminaire. It also measures the colour temperature, the colour rendering index at different angles, and generates several detailed photometric and colorimetric test reports for our luminaires.







CONTENTS

NOUVEAU NOIR	OUVEAU NOIR
VEGA NOUVEAU NOIR LED Cabinet Lighting	10
CUCINA LITE NOUVEAU NOIR LED Cabinet Lighting.	15
SIRIUS NOUVEAU NOIR LED Cabinet Lighting.	16
NOUVEAU NOIR Plinth Lighting	17
NOUVEAU NOIR Ceiling Lighting	18
NOUVEAU NOIR Power Ports.	20
SMART WIRELESS LIGHTING CONTROLS	
KINETIC SMART Lighting Controls	22
4 ZONE SMART Lighting Controls.	24
EASI-FIT SMART Lighting Controls.	26
MAGNETIC SMART Door Sensor	26
LED CABINET LIGHTING	
VEGA DIFFUSED LED Cabinet Lighting.	27
CUCINA-LITE MULTI POINT LED Cabinet Lighting.	32
SIRIUS DIFFUSED LED Cabinet Lighting.	37
SIRIUS TUNABLE DIFFUSED LED Cabinet Lighting.	44
SIRIUS CONNECT DIFFUSED LED Cabinet Lighting.	46
POLARIS CONNECT COB LED Cabinet Lighting.	48
HALO LED Cabinet Lighting.	50
240V CAPELLA LED Cabinet Lighting	52
240V TRICOLOUR LINK LIGHTS LED Cabinet Lighting	
240V LINK LIGHTS LED Cabinet Lighting.	55
LED FLEXIBLE STRIP	
COB TUNABLE WHITE LED Flexible Strip.	56
COB RGB COLOUR CHANGING LED Flexible Strip.	57
COB SUPERIOR LED Flexible Strip	58
COB STANDARD LED Flexible Strip.	59
ARC LED Flexible Strip.	60
FLEXILE LED Flexible Strip	61
5m & 3m IP20 REELS LED Flexible Strip	62
1m, 2m & 3m IP65 LED Flexible Strip.	63
ALUMINIUM EXTRUSION for LED Flexible Strip.	
BESPOKE LIGHTING SOLUTIONS	65
LED BATTERY LIGHTING	
NOVA LED Rechargeable Battery Lighting	66

CONTENTS

LED PLINTH LIGHTING	
VEGA LED Plinth Lighting	. 68
SIRIUS LED Plinth Lighting.	. 70
VERVE 15mm LED Plinth Lighting	72
LED DRAWER LIGHTING	
SENSOR LED Drawer Light	. 73
LED ILLUMINATED SHELVING	
VEGA LED Shelf.	. 74
SIRIUS LED Shelf.	
SIRIUS Clip on LED for Glass Shelving	76
PENDANT LIGHTING	
	77
CEILING LIGHTING	
CEILING Lighting.	86
POWER PORTS & WIRELESS CHARGING	
MOTORISED WITH SPEAKER Pop Up Sockets	
MOTORISED Pop Up Sockets.	
PULL UP POWERTECH PRO Pop Up Sockets	
PULL UP POWERTECH WITH SPEAKER Pop Up Sockets	
PULL UP Pop Up Sockets EVOLINE Pop Up Sockets	
EVOLINE Pack Flip.	
WIRELESS Qi Hidden Charger	
24V HIGH DEFINITION LIGHTING	
24V NOVA LED Cabinet Lighting	102
24V ORION LED Cabinet Lighting	
24V LED STRIP LED Flexible Strip.	
ACCESSORIES	
SWITCHES, SENSORS & DIMMERS.	111
LAMPS	115
POWER CONVERTERS	116
OTHER	
GLOSSARY	118
TEDMS AND CONDITIONS	110

NOUVEAU NOIR

MATT BLACK LIGHTING & ACCESSORY COLLECTION

We have introduced an on-trend collection of light fittings and accessories in a stylish matt black finish. This selection of stunning fittings would work well within a contemporary setting along side stylish dark coloured units and worktops for a sophisticated scheme.









ALL PRODUCTS ARE COVERED BY A 5-YEAR WARRANTY

Excludes battery operated products, power converters, accessories, pendants & motorised pop ups

VEGA MODA

DIFFUSED LED CABINET LIGHT





Exclusive to SycamoreLED.com, the Vega Moda is a discreet slim-line cabinet light with a diffused illuminated panel for a super smooth appearance. Available with matt black cover and an attractive edge lit feature, the Vega Moda would fit perfectly into a contemporary setting. Brushed nickel or white covers are available to purchase separate, see page 27 for more information.

PART CODE & DESCRIPTION

Vega Moda Matt Black/Natural White SY9805/BL

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights) SY9980B 15W 12Vdc LED Power Converter (1-6 lights) SY9739B

80mm 190mm

TECHNICAL INFO

Finish Matt Black 12Vdc **Power Supply** Cable Length 2m Colour Appearance Natural White Colour Temperature 4000K - 4500K Wattage 2.2W IP Rating IP20 Colour Rendering Index Ra >80 Total Lumens 150lm Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)

Wi-Fi 4 Zone Controls

Sensors, Switches & Dimmers

Page 24/25


Page 111 - 114

2m (SY7183) or 5m (SY7183/5) Extension Cable

VEGA MAX



DIFFUSED LED CABINET LIGHT



The Vega Max is a super slim diffused cabinet light with a magnetic bezel for ease of fitting. It has been designed to offer a superior light output and has a diffused cover with no visible LED points. The fitting also has enhanced curved edges in a stylish matt black finish. Also available in stainless steel finish, please see page 28.


PART CODE & DESCRIPTION

Vega Max Matt Black/ Warm or Natural White

SY8887BL/WW or NW

COMPATIBLE POWER CONVERTERS

15W 12Vdc LED Power Converter (1-3 lights)SY9739B20W 12Vdc LED Power Converter (1-4 lights)SY7350C30W 12Vdc LED Power Converter (1-6 lights)SY7715A



TECHNICAL INFO

Finish Matt Black
Power Supply 12Vdc

Cable Length 1.5m

Colour Appearance Warm White or Natural White
Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 5W IP Rating IP20 Colour Rendering Index Ra >80

Total Lumens WW - 499lm NW - 450lm

Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

VEGA FLAT PANEL



DIFFUSED LED CABINET LIGHT



The Vega has been designed to offer a superior light output and has a diffused cover to mimic the appearance of halogen cabinet lights with no visible LED points. The fitting also has unique magnetic fixing and enhanced curved edges. Available in Matt Black, and stainless steel (see page 29)

PART CODE & DESCRIPTION

Vega Flat Panel Matt Black/ Warm or Natural White

SY8949BL/WW or NW

COMPATIBLE POWER CONVERTERS


8W 12Vdc LED Power Converter (1-2 lights)

15W 12Vdc LED Power Converter (1-4 lights)

20W 12Vdc LED Power Converter (1-5 lights)

30W 12Vdc LED Power Converter (1-6 lights)

SY7715A



TECHNICAL INFO

Finish Matt Black
Power Supply 12Vac

Cable Length 1.5m

Colour Appearance Warm White or Natural White
Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 3.5W IP Rating IP20

Colour Rendering Index WW - Ra 93, NW - Ra 96

Total Lumens WW - 1851m, NW - 1981m

Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

VEGA DIFFUSED LED CABINET LIGHTS





These Vega LED Cabinet Lights are available in a recessed/surface option, or a slim-line designer tri-light. They both feature a diffused cover, so there are no visible LED points in the fitting, and also has a 120 degree beam angle which fills cabinets or work surfaces, eliminating dark spots. Now available in matt black finish. Other finish options are available on page 30/31.

PART CODE & DESCRIPTION

Vega Designer Tri-Light
Matt Black/Natural White SY7947BL/NW

Vega Recessed Matt Black/Natural White SY7945BL/NW


Vega Rec-Sur Matt Black/Natural White SY7946BL/NW


COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights) SY9980B 15W 12Vdc LED Power Converter (1-6 lights) SY9739B

TECHNICAL INFO

Finish Matt Black 12Vdc **Power Supply** Cable Length 2m Colour Appearance Natural White Colour Temperature 4000K - 4500K Wattage 2.3W IP Rating IP20 Colour Rendering Index Ra 89 185lm Total Lumens Beam Angle 120°





COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)
Page 22/23
Wi-Fi 4 Zone Controls
Page 24/25
Sensors, Switches & Dimmers
Page 111 - 114
2m (SY7183) or 5m (SY7183/5) Extension Cable

CUCINA LITE SOLARIS

MULTI POINT LED CABINET LIGHT





The multi point rectangular version of the Solaris surface mounted designer fitting has a super slim profile, in a stylish matt black finish. The Solaris also has a 120 degree beam angle, which fills cabinets or work surfaces and eliminates dark spots. Stainless steel finish available on page 33.

PART CODE & DESCRIPTION


Solaris Multi Point Recti Light Matt Black/Natural White SY7923BL

COMPATIBLE POWER CONVERTERS

15W 12Vdc LED Power Converter (1-3 lights)SY9739B20W 12Vdc LED Power Converter (1-4 lights)SY7350C30W 12Vdc LED Power Converter (1-6 lights)SY7715A

TECHNICAL INFO

Matt Black Finish **Power Supply** 12Vdc Cable Length 1.5m Colour Appearance Natural White 4000K - 4500K Colour Temperature 5W Wattage IP Rating IP20 Colour Rendering Index Ra 85 Total Lumens 481lm Beam Angle 120°



COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)
Wi-Fi 4 Zone Controls
Page 22/23
Page 24/25
Sensors, Switches & Dimmers
Page 111 - 114
Page (SY7183) or 5m (SY7183/5) Extension Cable

SIRIUS SUPER SLIM DIFFUSED LED CABINET LIGHT



PART CODE & DESCRIPTION

Sirius Super Slim Matt Black/Warm White SY8935A/BLWW Sirius Super Slim Matt Black/Natural White SY8935A/BL

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights) SY9980B 15W 12Vdc LED Power Converter (1-6 lights) SY9739B



This diffused cabinet light is surface mounted and has a super slim design with a magnetic cover to conceal the installation fixings. This sleek matt black fitting is available in a choice of natural white or warm white. Stainless steel finish available on page 40.

TECHNICAL INFO

Finish Matt Black
Power Supply 12Vdc
Cable Length 1.5m

Colour Appearance Warm or Natural White

Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 2W IP Rating IP20

Colour Rendering Index WW - Ra 80, NW - Ra 86
Total Lumens WW - 125lm, NW - 143lm

Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)

Page 22/23


Wi-Fi 4 Zone Controls

Page 24/25

Sensors, Switches & Dimmers

Page 111 - 114

2m (SY7183) or 5m (SY7183/5) Extension Cable



SIRIUS SUPER SLIM DIFFUSED LED CABINET LIGHT



PART CODE & DESCRIPTION

Sirius Super Slim Angled Matt Black/Warm White

SY8935B/2700K

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights) SY9980B 15W 12Vdc LED Power Converter (1-6 lights) SY9739B

C € CK ⊕ CF W Z ROHS


This diffused angled cabinet light is surface mounted and has a super slim design with a magnetic cover to conceal the installation fixings. Available only in warm white 2700K.

TECHNICAL INFO

Finish Matt Black 12Vdc **Power Supply** Cable Length 1.5m Colour Appearance Warm White Colour Temperature 2700K Wattage 2W IP20 IP Rating Colour Rendering Index Ra 81 Total Lumens 52lm Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)
Page 22/23
Wi-Fi 4 Zone Controls
Page 24/25
Sensors, Switches & Dimmers
Page 111 - 114
2m (SY7183) or 5m (SY7183/5) Extension Cable





SIRIUS SOLARIS DIFFUSED LED CABINET LIGHT



PART CODE & DESCRIPTION

Solaris Diffused Recti Light Matt Black

SY8951BL

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-2 lights) SY9980B 15W 12Vdc LED Power Converter (1-4 lights) SY9739B 20W 12Vdc LED Power Converter (1-5 lights) SY7350C 30W 12Vdc LED Power Converter (1-6 lights) SY7715A



The diffused rectangular version of the Solaris surface mounted designer fitting has a super slim profile, in a stylish matt black finish. The Solaris also has a 120 degree beam angle, which fills cabinets or work surfaces and eliminates dark spots. Stainless steel finish available on page 39.

TECHNICAL INFO


Finish Matt Black 12Vdc **Power Supply** Cable Length 1.5m

Colour Appearance Natural White Colour Temperature 4000K - 4500K


Wattage 3.5W IP Rating IP20 Colour Rendering Index Ra 87 Total Lumens 156lm Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming) Page 22/23 Wi-Fi 4 Zone Controls Page 24/25 Page 111 - 114 Sensors, Switches & Dimmers 2m (SY7183) or 5m (SY7183/5) Extension Cable



VERVE 15mm DIFFUSED LED PLINTH LIGHT



PART CODE & DESCRIPTION

4 Light Kit (Stainless) Warm/Cool 10 Light Kit (Stainless) Warm/Cool Individual (Stainless) Warm/Cool

SY9936WW or CW SY9928A/WW or CW SY9937WW or CW

For black finish please purchase kit required from above, and purchase the covers separate, listed below.

Black Cover (individual)

SY9939BK



This small and discreet recessed plinth light is now available with a matt black finish, and with either cool or warm white LED.

The 15mm plinth lights are available in a 4 or 10 light kit, which includes the power converter, Add on lights are also available, up to a maximum of 10 lights can be run per power converter.

TECHNICAL INFO

Finish Stainless Steel/Matt Black

Power Supply 12Vdc (included)

Cable Length 1.5m

Colour Appearance Warm or Cool White


3000K - 3500K or 6000K or 6500K Colour Temperature

Wattage 0.2W per fitting

IP Rating IP67

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming) Page 22/23 Wi-Fi 4 Zone Controls Page 24/25 Sensors, Switches & Dimmers Page 111 - 114




6W SWITCHABLE

DIMMABLE

IP65 FIRE RATED DOWNLIGHT







Choose from 3000k, 4000k or 6000k by simply choosing your preference using the integrated switch on the front of the fitting. It is also fully dimmable from most standard wall dimmers, and also includes the power converter. The light output is equivalent to a 50W GU10 halogen lamp, but due to the latest LED technology it uses 85% less energy, helping to save money and the environment.

This ultra slim fitting is designed to allow loft insulation to be continuously run over the back of the fitting (IC Rated), and features a speed fit tool free loop in - loop out terminal. The colour appearance can be changed at any time without removing the fitting from the ceiling by simply removing the bezel.

Power Converter Included

TECHNICAL INFO

Power Supply 240V

Colour Appearance Switchable - Warm, Natural or

Coo

Colour Temperature Switchable - 3000K, 4000K or

6000K

Wattage 6W Beam Angle 40°

Total Lumens WW - 593lm NW - 680lm,

CW - 635lm

IP Rating IP65

Colour Rendering Index >Ra 80

Finish White (Matt Black* available to

purchase separate)

Cut Out Size 65mm

*Other finishes available, please see page 86.

PART CODE & DESCRIPTION

6W Switchable Downlight White SY9050WH

ADDITIONAL MATT BLACK BEZEL

Matt Black Bezel SY9051BK

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)

Page 22/23



8W SWITCHABLE

DIMMABLE 1P65 FIRE RATED DOWNLIGHT



PART CODE & DESCRIPTION

8W Switchable Downlight White

SY9004WH

ADDITIONAL MATT BLACK BEZEL

Matt Black Bezel

SY9005BL

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)

Page 22/23

Choose from 3000k, 4000k or 6000k by simply choosing your preference using the integrated switch on the fitting. It is also fully dimmable from most standard wall dimmers, and also includes the power converter. The light output is equivalent to a 50W GU10 halogen lamp, but due to the latest LED technology it uses 85% less energy, helping to save money and the environment.

The fitting is designed to allow loft insulation to be continuously run over the back of the fitting (IC Rated), and features a loop in - loop out clip block

Power Converter Included



TECHNICAL INFO

Power Supply 240V

Colour Appearance Switchable - Warm, Natural or

Cool

Colour Temperature Switchable - 3000K, 4000K or

6000K

Wattage 8W
Beam Angle 60°

Total Lumens WW - 782lm NW - 916lm, CW -

805lm

IP RatingIP65Colour Rendering Index>Ra 80

Finish White (Matt Black* available to

purchase separate)

Cut Out Size 70mm

*Other finishes available, please see page 87.

OW DIMMABLE IP65 FIRE RATED DOWNLIGHT



PART CODE & DESCRIPTION 6W Downlight Warm White

6W Downlight Natural White

SY9057WW SY9057NW

ADDITIONAL MATT BLACK BEZE

SY9051BK

COMPATIBLE ACCESSORIES

Matt Black Bezel

Kinetic Wireless Switching (inc. dimming)

Page 22/23

This ultra slim fitting is designed to allow loft insulation to be continuously run over the back of the fitting (IC Rated), and features a speed fit tool free loop in - loop out terminal.

The fitting comes complete with a white bezel, but other colour options are also available to purchase separate, listed below.

Available in either warm or natural white, It is also fully dimmable from most standard wall dimmers, and also includes the power converter. The light output is equivalent to a 50W GU10 halogen lamp, but due to the latest LED technology it uses 85% less energy, helping to save money and the environment.

Power Converter Included



TECHNICAL INFO

Power Supply 240V

Colour Appearance Warm or Natural White

Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 6W
Beam Angle 40°
Total Lumens 600Im
IP Rating IP65

Colour Rendering Index >Ra 80

Finish White (Matt Black* available to

purchase separate)

Cut Out Size 68mm - 70mm

^{*}Other finishes available, please see page 88.

MOTORISED

POP UP SOCKET WITH SPEAKER



CELK TOHS

MOTORISED POP UP SOCKET



CELK LATER OF THE ROHS

This motorised socket is available in a stylish black finish with a black glass top. The unit is motorised, simply touch the lid and the unit will rise. It also features an anti trap safety feature which stops the unit from closing when it senses an object

The built in Bluetooth Speakers enable users to stream music from connected devices, and a Qi Charger is built into the lid to charge Qi enabled devices (will only charge when the unit is in the closed position).

TECHNICAL INFO

Finish Black with Black Glass Top

Wireless Charging Qi
UK Sockets 2

USB Ports 1 x USB-A (2.1A) & 1 x USB-C (3.0A)

Cable Length 1.9m
Guarantee 12 Months
Cut Out Size 95mm

PART CODE & DESCRIPTION

Motorised Pop Up Socket with Speaker/ USB/Qi Charging with Black Glass Top SY9019BK/SPEAKER



Silver model also available, please refer to page 90.

This motorised socket is available in a stylish black finish with a black glass top. The unit is motorised, simply touch the lid and the unit will rise. It also features an anti trap safety feature which stops the unit from closing when it senses an object

A Qi Charger is built into the lid to charge Qi enabled devices (will only charge when the unit is in the closed position).

TECHNICAL INFO

Finish Black with Black Glass Top

Wireless Charging Qi
UK Sockets 3

USB Ports 1 x USB-A (2.1A) & 1 x USB-C (3.0A)

Cable Length 1.9m
Guarantee 12 Months
Cut Out Size 95mm

PART CODE & DESCRIPTION

Motorised Pop Up Socket with USB/ Qi Charging with Black Glass Top

SY9019BK



Silver & White model also available, please refer to page 93.

POWERTECH PRO

FLUSH PULL UP SOCKET



This new version of the powertech module pulls up to reveal 3 UK sockets and 2 USB ports. It also features Qi wireless charging when the module is in any position.

The super-slim top is nearly flush with the work surface making it blend in with the surrounding environment, and is available in either a sleek black glass top or a stainless steel effect top (See page 94 for stainless steel version).

PART CODE & DESCRIPTION

Powertech Pro Pull Up Module with Qi Charging & Black Top

SY9058BL

TECHNICAL INFO

Finish Black
Wireless Charging Qi
UK Sockets 3

USB Ports 1 x USB-C (3.0A) & 1 X USB-A (2.1A)

Cable Length 2m Cut Out Size 95mm



Stainless Steel model also available, please refer to page 94.

EVOLINE BACK FLIP



CELA LA CARRONS

Compact and flush fitting, the EVOline Backflip provides access to discreet power connectivity, wherever it may be needed. Installed into a worktop and/or above most drawers, the EVOline Backflip turns effortlessly with the press of a finger to reveal 2 UK power sockets and a USB charging point.

Other finishes are available, please see page 100.

TECHNICAL INFO

Finish Black Steel/Black Glass

UK Sockets 2

USB Ports 1 x USB-C (USB-A still available to order)

Guarantee 12 Months
Cut Out Size 88mm x 215mm

PART CODE & DESCRIPTION

Evoline Back Flip Black Steel SY9736BS/C
Evoline Back Flip Black Glass SY9736BK/C



WIRELESS KINETIC

SMART CONTROLS



Control either 12/24V lighting, or 240V lighting including Ceiling Lighting, Pendant Lighting & Extractor fans, in the following ways;



Wireless Wall Plate Switch

(No wiring or batteries required)



Smart Phone or Tablet



Alexa or Google Voice Control

Look for the logos for compatible products







The new wireless Kinetic Switching system allows users to turn on their kitchen, bedroom or bathroom lighting in three different ways.

Lighting can be controlled manually by using the Wireless Kinetic Switch, through a Smart Phone or Tablet using the Smart Life App (free downloadable App via the QR code on the instruction leaflet), or by connecting it to a voice controlled intelligent personal assistant such as Amazon Alexa or Google Home.

Once connected, lighting can be operated with simple commands, such as "Alexa turn on kitchen lights" or "Google dim strip lights".

EASY DIMMING

Dimming is also possible, by using the 12V/24Vdc furniture lighting receiver with built in dimming facility. 240V LED Lighting (with dimmable lamp fitted), and dimmable ceiling lighting can also be controlled using the 240v receiver. Simply holding down the switch activates the dimming process.

ENERGY SAVING

A small amount of kinetic energy is generated by the action of the clicking of the switch, which is converted to an electrical signal and sent to the receiver. The amount of energy used is very low, so the switch adheres to strict requirements on low power consumption & helps the environment.

WIRELESS SWITCHES - EASY TO INSTALL & RETRO-FIT

The Kinetic switches require no wiring or batteries which eliminates the need for installing back boxes, creating channels in walls and adjusting decor, thus speeding up the installation process and reducing labour time & costs.

The switch can be installed anywhere in the home, including the bathroom due to its IP67 rating. It can also be installed on a variety of surfaces, including glass, marble, ceramic tiles, and other smooth surfaces. The switches can be screwed to the surface, or stuck on with the adhesive pads supplied.

They can also be retro-fit onto existing back boxes as they are the same size as standard switches.









WIRELESS KINETIC DOOR SENSOR

The Kinetic Wireless door sensor switch (SY2446) is a battery free contact switch to turn lights on and off, so no batteries or wires are required.

When the door is opened the connected light switches on via a kinetic energy transfer to the receiver. Receiver or smart power converter required.

Download the Smart Life app here:





ANDROID



12V/24V FURNITURE LIGHTING

SMART WIRELESS RECEIVER

This receiver can be used to switch or dim 12/24vdc LED lighting.



ECHNICAL INFO

Power Supply 12/24Vdd


//aximum Load 12Vdc - 36W

24Vdc - 72W

PART CODE & DESCRIPTION

12/24Vdc Furniture Lighting Receiver

Y2416



240V LIGHTING

SMART WIRELESS RECEIVER

This receiver can be used to switch 240V LED lighting, including ceiling lighting, pendant lighting & bathroom fans. You can also dim connected lights (with a dimmable light source).



FECHNICAL INFO

Power Supply


wer Supply 240

Maximum Load 100W

PART CODE & DESCRIPTION

240V Lighting Receiver

SY8989/NFW



SMART KINETIC POWER CONVERTERS



The smart all-in-one drivers combine the functionality of the 12Vdc furniture kinetic receiver, with a dimmable driver for low loads of 15W or 20W or less. This driver can be used with the kinetic wireless wall plate switches, or with the smart App or voice control.

PART CODE & DESCRIPTION

15W 12Vdc Smart All-in-One Driver20W 12Vdc Smart All-in-One DriverSY8999

WIRELESS KINETIC SWITCHES





TECHNICAL INFO

Finish White
IP Rating IP67
Connection Wireless

Fixing Method Adhesive Backing or Screw

PART CODE & DESCRIPTION

1 Gang Kinetic Switch2 Gang Kinetic Switch3 Gang Kinetic Switch5Y89915Y8992

WIRELESS KINETIC DOOR SENSOR



TECHNICAL INFO

Finish White
IP Rating IP20
Connection Wireless

Fixing Method Adhesive Backing

PART CODE & DESCRIPTION

Kinetic Wireless Door Sensor SY2446

WIRELESS 4 ZONE

SMART CONTROLS



Control 12/24Vdc LED lighting in the following ways;



Remote Control



Smart Phone or Tablet

(Using a free App)



Wireless Wall Plate Switch
(No wiring required)

Our innovative 4 zone remote control system allows wireless control of multiple LED lights in the palm of your hand, using a hand held remote, a smart device, or a wall mounted controller.

The new style receiver features built in Wi-Fi capabilities, so you can control your cabinet lights, plinth lights, strip lighting or any other 12/24Vdc lighting using your smart device, by downloading the App, which is free via the Apple store or Android Google Play. This will allow you to control your connected lights from anywhere in the world as long as you have a 4G or 5G network, or connected to any Wi-Fi network at your location.

SINGLE COLOUR 4 ZONE

The single colour 4 zone controls can be used with either 12V or 24Vdc lighting.

Control up to 4 different zones of lighting, by using the remote control, a smartphone or tablet, or a wall mounted wall switch.

Dimming is possible by simply holding down the relevant zone button.

The receiver now features built in Wi-Fi capabilities to enable control on a smart device via a free downloadable app.

TUNABLE WHITE (CCT) 4 ZONE

Our Tunable White (CCT (Correlated Colour Temperature)) 4 zone controls can be used with our tunable white collection of LED Lighting;

Tunable LED Cabinet Lighting - Page 44 & 45 Tunable COB LED Flexible Strip Lighting - Page 56

Control up to 4 different zones of lighting, by using the remote control, a smartphone or tablet, or a wall mounted wall switch Users can change the colour of their LED lighting from warm white, to natural white and through to cool white. Dimming is possible by simply holding down the relevant zone button.

The receiver now features built in Wi-Fi capabilities to enable control on a smart device via a free downloadable app.

RGB COLOUR CHANGING 4 ZONE

This RGB 4 zone controls can be used with our RGB Colour Changing LED Strip;

RGB COB LED Flexible Strip Lighting - Page 57

Control up to 4 different zones of lighting, by using the remote control, a smartphone or tablet, or a wall mounted wall switch.

Users have control of a full colour range, with up to 16 million colour possibilities including standard RGB colours plus saturation and dimming.

The receiver now features built in Wi-Fi capabilities to enable control on a smart device via a free downloadable app.

WIRELESS 4 ZONE

SMART CONTROLS

SINGLE COLOUR SINGLE ZONE




PART CODE & DESCRIPTION

(a) Single Zone Single Colour Receiver SY8120 (b) Dimming/on/off Black Wall Plate SY8121

This single zone/colour receiver can be used to control lights which are 240V. It can also be controlled by our standard remote control (c) SY9565, and/or the rotary dimmer switch (b) SY8121.

SINGLE COLOUR 4 ZONE



PART CODE & DESCRIPTION


(c + d) Single Colour Receiver & Remote Kit (Wi-Fi Series) SY7541B SY7542B (d) Additional Receiver (e) Wireless Wall Plate (White) SY8810/DIM New black accessories listed below

(f) Wireless Wall Plate (Black) SY8810DIM BL

TECHNICAL INFO

Total Output Max 12A

TUNABLE WHITE (CCT) 4 ZONE



PART CODE & DESCRIPTION

(c + g) Tunable White Receiver & Remote Kit (Wi-Fi Series) SY5699B (g) Additional Receiver SY7699B

(h)Wireless Wall Plate (White) SY8810/TUNABLE

TECHNICAL INFO

Total Output Max 12A

RGB COLOUR CHANGING 4 ZONE



PART CODE & DESCRIPTION

RGB Colour Changing Receiver & Remote Kit (Wi-Fi Series) White (i + j) or Black (k + j)

(j) Additional Receiver

(I) Wireless Wall Plate (White) New black accessories listed below

(m) Wireless Wall Plate (Black)

SY7598B/WH or BL

SY7538B

SY8810/RGB

SY8810RGBW BL

TECHNICAL INFO

Total Output Max 12A


WIRELESS CONTROLS

EASI-FIT SMART REMOTE CONTROL



PART CODE & DESCRIPTION

Wireless Smart Remote SY9940
Smart Distribution Block SY9941



This wireless remote control allows users to switch or dim 12/24Vdc LED lighting by simply touching the button on the circular remote.

A magnetic pad is also supplied to easily mount the remote control onto a wall or cabinet if required.

The 10 port distribution block features a plug and play system for ease of installation.

Remote includes 3V battery.

TECHNICAL INFO

Finish	White
Power Supply	12/24Vdc
Cable Length	100mm
Guarantee	12 Months
Sensor Distance	20m max
Wattage	100W max

MAGNETIC DOOR SENSOR



PART CODE & DESCRIPTION

Single Door Sensor Kit

Double Door Sensor Kit

SY2449/2

Triple Door Sensor Kit

SY2449/3


Quad Door Sensor Kit

SY2449/4

Kits include 1 x controller (b) and specified number of magnetic door sensor switches (a)

12 Way Distribution Block (c)

SY7637



This wireless magnetic door sensor switch can turn lights on and off automatically. The switch is secured to the inside of a cabinet using the adhesive back, whilst the separate magnetic contact button is placed on the inside of the door. When the door closes the connected lights automatically switch off. Opening the door prompts the lights to turn back on.

Up to 4 switches can be run from one controller, making it perfect for switching lights on and off within kitchen cabinets. The switch runs on two 3V button batteries which are very easy to change when required. Unit includes connection for one light, a 12 Way Distribution Block can be purchased separately if required.

TECHNICAL INFO

TECHNICAL INFO			
Finish	Silver		
Power Supply	12/24Vdc		
Cable Length	200mm		
Guarantee	12 Months		
Max Current	8mA		
Sensor Distance	5m		
Wattage	12Vdc - 36W/24Vdc - 72W		
IP Rating	IP20		









VEGA MODA



DIFFUSED LED CABINET LIGHT



Exclusive to SycamoreLED.com, the Vega Moda is a discreet slim-line cabinet light with a diffused illuminated panel for a super smooth appearance. Available with either matt black, brushed nickel or white magnetic bezels, and an attractive edge lit feature, the Vega Moda would fit perfectly into a contemporary setting.

PART CODE & DESCRIPTION

Vega Moda Matt Black/Natural White SY9805/BL


For brushed nickel or white finish please purchase light above, and purchase the covers separate, listed below

Vega Moda Brushed Nickel Cover SY9806/BN

Vega Moda White Cover SY9806/WH

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights) SY9980B 15W 12Vdc LED Power Converter (1-6 lights) SY9739B



TECHNICAL INFO

Finish Matt Black/Brushed Nickel/White

12Vdc **Power Supply** 2m

Cable Length

Natural White Colour Appearance Colour Temperature 4000K - 4500K

Wattage 2.2W IP Rating IP20 Colour Rendering Index Ra 87 Total Lumens 150lm Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming) Page 22/23 Wi-Fi 4 Zone Controls Page 24/25 Sensors, Switches & Dimmers Page 111 - 114 2m (SY7183) or 5m (SY7183/5) Extension Cable

VEGA MAX



DIFFUSED LED CABINET LIGHT



The Vega Max is a super slim diffused cabinet light with a magnetic bezel for ease of fitting. It has been designed to offer a superior light output and has a diffused cover with no visible LED points. The fitting also has enhanced curved edges in a stylish matt black or brushed nickel finish.

PART CODE & DESCRIPTION

Vega Max Brushed Nickel/ Warm or Natural White

SY8887WW or NW

Vega Max Matt Black/ Warm or Natural White

SY8887BL/WW or NW

COMPATIBLE POWER CONVERTERS

15W 12Vdc LED Power Converter (1-3 lights)SY9739B20W 12Vdc LED Power Converter (1-4 lights)SY7350C30W 12Vdc LED Power Converter (1-6 lights)SY7715A

100mm

TECHNICAL INFO

Finish Matt Black/Brushed Nickel

Power Supply 12Vdc Cable Length 1.5m

Colour AppearanceWarm White or Natural WhiteColour Temperature3000K - 3500K or 4000K - 4500K

Total Lumens WW - 499lm, NW - 450lm

Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

VEGA FLAT PANEL



DIFFUSED LED CABINET LIGHT



The Vega has been designed to offer a superior light output and has a diffused cover to mimic the appearance of halogen cabinet lights with no visible LED points. The fitting also has unique magnetic fixing and enhanced curved edges. Available in Brushed Nickel and Matt Black.


PART CODE & DESCRIPTION

Vega Flat Panel Brushed Nickel/
Warm or Natural White SY8949BN/WW or NW

Vega Flat Panel Matt Black/
Warm or Natural White SY8949BL/WW or NW

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-2 lights) SY9980B 15W 12Vdc LED Power Converter (1-4 lights) SY9739B 20W 12Vdc LED Power Converter (1-5 lights) SY7350C 30W 12Vdc LED Power Converter (1-6 lights) SY7715A



TECHNICAL INFO

Finish Brushed Nickel/Matt Black
Power Supply 12Vdc
Cable Length 1.5m
Colour Appearance Warm White or Natural White
Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 3.5W IP Rating IP20

Colour Rendering Index WW - Ra 93, Ra 96

Total Lumens WW - 185lm NW - 198lm

Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114



VEGA

DIFFUSED LED CABINET LIGHTS



The Vega collection offers a superior light output and has a diffused cover to mimic the appearance of halogen cabinet lights, with no visible LED points. It also has a 120 degree beam angle, which fills cabinets or work surfaces, and eliminates dark spots.

Now available in matt black finish with natural white LED (Recessed/Surface & Designer Tri-Light only).

TECHNICAL INFO

Finish Brushed Nickel (Black finish

options listed on page 14)

Power Supply 12Vdc Cable Length 2m

Colour Appearance Warm White or Natural White
Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 2.3W IP Rating IP20

Colour Rendering Index WW - Ra 84, NW - Ra 89
Total Lumens WW - 171 Im NW - 185 Im

Beam Angle 120°



COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights) SY9980B 15W 12Vdc LED Power Converter (1-6 lights) SY9739B

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)
Page 22/23
Wi-Fi 4 Zone Controls
Page 24/25
Sensors, Switches & Dimmers
Page 111 - 114




DESIGNER TRI-LIGHT

PART CODE & DESCRIPTION

Vega LED Designer Tri-Light Warm/Natural White

SY7947WW or NW



Now available in matt black finish with natural white LED (see page 14)




TRI-LIGHT

PART CODE & DESCRIPTION

Vega LED Tri-Light Warm/Natural White

SY7980WW or NW






DESIGNER RECTI-LIGHT

PART CODE & DESCRIPTION

Vega LED Designer Recti-Light Warm/Natural White

SY6881WW or NW





RECESSED

PART CODE & DESCRIPTION

Vega LED Recessed Warm/Natural White

SY7945BN/WW or NW

12.4mm

Now available in matt black finish with natural white LED (see page 14)



RECESSED/SURFACE

PART CODE & DESCRIPTION

Vega LED Recessed/Surface Warm/Natural White

SY7946BN/WW or NW



Now available in matt black finish with natural white LED (see page 14)

CUCINA LITE SOLARIS SQUARE

MULTI POINT LED CABINET LIGHT



This surface mounted designer fitting has a slim profile, in a sleek aluminium finish. Available in a modern square design, this fitting would look perfect in a contemporary setting. The natural white LED is suitable for any type of kitchen design. The Solaris also has a 120 degree beam angle, which fills cabinets or work surfaces, and eliminates dark spots.

PART CODE & DESCRIPTION

Solaris Square Multi Point LED Cabinet Light/ Natural White

SY7922

COMPATIBLE POWER CONVERTERS

15W 12Vdc LED Power Converter (1-3 lights)SY9739B20W 12Vdc LED Power Converter (1-4 lights)SY7350C30W 12Vdc LED Power Converter (1-6 lights)SY7715A

TECHNICAL INFO

Finish Aluminium 12Vdc **Power Supply** Cable Length 1.5m Natural White Colour Appearance Colour Temperature 4000K - 4500K Wattage 5W IP Rating IP20 Colour Rendering Index Ra 85 Total Lumens 487lm Beam Angle 120°

75mm

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

CUCINA LITE SOLARIS RECTI

MULTI POINT LED CABINET LIGHT



The rectangular version of the Solaris surface mounted designer fitting has a slim profile, in a sleek aluminium finish. This fitting would look perfect in a contemporary setting, and the natural white LED is suitable for any type of kitchen design. The Solaris also has a 120 degree beam angle, which fills cabinets or work surfaces, and eliminates dark spots.


PART CODE & DESCRIPTION

Solaris Recti Multi Point LED Cabinet Light
Aluminium/Natural White SY7923

Solaris Recti Multi Point LED Cabinet Light
Matt Black/Natural White SY7923BL

COMPATIBLE POWER CONVERTERS

15W 12Vdc LED Power Converter (1-3 lights)SY9739B20W 12Vdc LED Power Converter (1-4 lights)SY7350C30W 12Vdc LED Power Converter (1-6 lights)SY7715A



TECHNICAL INFO

Finish Aluminium/Matt Black 12Vdc **Power Supply** Cable Length 1.5m Natural White Colour Appearance 4000K - 4500K Colour Temperature Wattage 5W IP Rating IP20 Ra 85 Colour Rendering Index Total Lumens 481lm Beam Anale 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)

Wi-Fi 4 Zone Controls

Sensors, Switches & Dimmers

Page 22/23

Page 24/25

Page 111 - 114

2m (SY7183) or 5m (SY7183/5) Extension Cable

CUCINA LITE

(€UK ⊕ ☐ FOHS

MULTI POINT LED CABINET LIGHT



This collection of LED cabinet lights offers a choice of cool or warm white LED, with a variety of different style bodies to suit different applications or tastes. The LED offers a good quality light output, enabling them to be used as task lighting in a kitchen, as well as adding mood lighting to any application.

TECHNICAL INFO

Finish Chrome or Brushed Nickel

Power Supply 12Vdc Cable Length 2m

Colour Appearance Warm White or Cool White
Colour Temperature 3000K - 3500K or 6000K - 6500K

Wattage 1.8W IP Rating IP44

Colour Rendering Index WW - Ra 81, CW - Ra 85

Total Lumens WW - 165lm, CW - 168lm

Beam Angle 65°



COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights) SY9980B 15W 12Vdc LED Power Converter (1-6 lights) SY9739B

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114




DESIGNER TRI-LIGHT

PART CODE & DESCRIPTION

Como LED Designer Tri-Light
Brushed Nickel/Warm or Cool White

SY9979WW or CW






TRI-LIGHT

PART CODE & DESCRIPTION

Trieste LED Tri-Light

Brushed Nickel/Warm or Cool White

SY7155A/WW or CW






DESIGNER RECTI-LIGHT

PART CODE & DESCRIPTION

Cucina Lite LED Designer Recti Brushed Nickel/Warm or Cool White

SY7883WW or CW





RECESSED

PART CODE & DESCRIPTION

Chrome/Warm or Cool White


Rimini LED Recessed

Rimini LED Recessed

Brushed Nickel/Warm or Cool White

SY7180NM/WW or CW

SY7180CC/WW or CW







PART CODE & DESCRIPTION

Rimini LED Recessed/Surface

Brushed Nickel/Warm or Cool White

Rimini LED Recessed/Surface Chrome/Warm or Cool White SY9978NM/WW or CW

SY9978CC/WW or CW



Spacer depth

CUCINA LITE TOUCH (EXAMPLE ROHS



MULTI POINT LED CABINET LIGHT




This LED cabinet lights features a simple on/off feature, by simply touching the fitting itself. Available in recessed only, it offers a choice of natural or warm white LED. This fitting should not be installed in conductive surfaces.

PART CODE & DESCRIPTION

Rimini Touch on/off SY7815BN/WW or NW

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights) SY9980B 15W 12Vdc LED Power Converter (1-6 lights) SY9739B



TECHNICAL INFO

Finish Brushed Nickel

12Vdc **Power Supply** Cable Length 2m

Warm White or Natural White Colour Appearance 3000K - 3500K or 4000K - 4500K Colour Temperature

1.8W Wattage IP Rating IP44

Colour Rendering Index WW - Ra 81, NW - Ra 83 Total Lumens WW - 104lm, NW - 113lm

Beam Angle 55°

Resistance 80 Ohms Current 0.15 Amps

COMPATIBLE ACCESSORIES

SIRIUS TABLET



DIFFUSED LED CABINET LIGHT




The slimline Sirius tablet style cabinet light offers a superior light output, and has no visible LED points due to the diffused style cover. The panel is only 6mm thick, and is easily installed by fixing the metal plate to the cabinet, and the light magnetically attaches itself to the plate. It can also be easily removed for cleaning. A 500mm connecting cable is available to link each light together.

PART CODE & DESCRIPTION

Sirius Tablet Style White Natural White	SY7963
500mm Connecting Cable	SY7964

COMPATIBLE POWER CONVERTERS

15W 12Vdc LED Power Converter (1-3 lights)	SY9739B
20W 12Vdc LED Power Converter (1-4 lights)	SY7350C
30W 12Vdc LED Power Converter (1-6 lights)	SY7715A



TECHNICAL INFO

Finish	White
Power Supply	12Vdc
Cable Length	1.5m
Colour Appearance	Natural White
Colour Temperature	4000K - 4500K
Wattage	5W
IP Rating	IP20
Colour Rendering Index	Ra 88
Total Lumens	248lm
Beam Angle	110°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)	Page 22/23	
Wi-Fi 4 Zone Controls	Page 24/25	
Sensors, Switches & Dimmers	Page 111 - 114	
2m (SY7183) or 5m (SY7183/5) Extension Cable		

SIRIUS SOLARIS SQUARE

DIFFUSED LED CABINET LIGHT






The square version of the Solaris surface mounted designer fitting has a slim profile and a sleek aluminium finish. This fitting would look perfect in all kitchen settings and the natural white LED is suitable for any type of kitchen design. The Solaris also has a 120 degree beam angle, which fills cabinets or work surfaces and eliminates dark spots.

PART CODE & DESCRIPTION

Solaris Square Diffused LED Cabinet Light/
Natural White SY8950

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-2 lights) SY9980B
15W 12Vdc LED Power Converter (1-4 lights) SY9739B
20W 12Vdc LED Power Converter (1-5 lights) SY7350C
30W 12Vdc LED Power Converter (1-6 lights) SY7715A



TECHNICAL INFO

Finish Aluminium **Power Supply** 12Vdc Cable Length 1.5m Natural White Colour Appearance Colour Temperature 4000K - 4500K Wattage 3.5W IP Rating IP20 Colour Rendering Index Ra 86 Total Lumens 157lm Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)

Wi-Fi 4 Zone Controls

Sensors, Switches & Dimmers

2m (SY7183) or 5m (SY7183/5) Extension Cable

SIRIUS SOLARIS RECTI

DIFFUSED LED CABINET LIGHT





The rectangular version of the Solaris surface mounted designer fitting has a super slim profile, in a sleek aluminium finish. The Solaris also has a 120 degree beam angle, which fills cabinets or work surfaces and eliminates dark spots.

PART CODE & DESCRIPTION


Solaris Recti Diffused LED Cabinet light
Aluminium/Natural White SY8951

Solaris Recti Diffused LED Cabinet light

Matt Black/Natural White SY8951BL

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-2 lights)SY9980B15W 12Vdc LED Power Converter (1-4 lights)SY9739B20W 12Vdc LED Power Converter (1-5 lights)SY7350C30W 12Vdc LED Power Converter (1-6 lights)SY7715A



TECHNICAL INFO

Finish Aluminium/Matt Black

Power Supply 12Vdc Cable Length 1.5m

Colour Appearance Natural White
Colour Temperature 4000K - 4500K

Wattage 3.5W
IP Rating IP20
Colour Rendering Index Ra 87
Total Lumens 156Im
Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

SIRIUS SUPER SLIM



DIFFUSED LED CABINET LIGHT



This diffused cabinet light is surface mounted and has a super slim design with a magnetic cover to conceal the installation fixings. This sleek brushed steel or matt black fitting is available in a choice of natural white or warm white.

PART CODE & DESCRIPTION

Sirius Super Slim Brushed Nickel/ Warm or Natural White

SY8935A/WW or NW


Sirius Super Slim Matt Black/ Warm or Natural White

SY8935A/BLWW or NW

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights)
15W 12Vdc LED Power Converter (1-6 lights)

SY9980B SY9739B



TECHNICAL INFO

Finish Brushed Nickel/Matt Black

Power Supply 12Vdc Cable Length 1.5m

Colour Appearance Warm White or Natural White
Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 2W IP Rating IP20

Colour Rendering Index WW - Ra 80 NW - Ra 86

Total Lumens WW - 125Im NW - 143Im

Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

SIRIUS SLIMLINE SENSOR

DIFFUSED LED CABINET LIGHT

CELK TOHS



The infra red sensor light has an integrated movement sensor that activates the LED light when a door is opened. It also automatically switches off when no movement has been detected within 60 seconds. The fitting is ideal for surface mounting inside kitchen cabinets or wardrobes. Detection range is 1 m.

PART CODE & DESCRIPTION

Slimline Infra Red Sensor LED Cabinet Light SY7786

COMPATIBLE POWER CONVERTERS


8W 12Vdc LED Power Converter (1-2 lights)SY9980B15W 12Vdc LED Power Converter (1-5 lights)SY9739B20W 12Vdc LED Power Converter (1-6 lights)SY7350C

TECHNICAL INFO

Beam Angle

Aluminium Finish **Power Supply** 12Vdc Cable Length 2m Colour Appearance Natural White 4000K - 4500K Colour Temperature Wattage 3W IP Rating IP20 Colour Rendering Index Ra >80

115°





COMPATIBLE ACCESSORIES

SIRIUS



DIFFUSED LED CABINET LIGHTS



The Sirius Range is at the forefront of modern technology, offering an ideal alternative to halogen lights. Designed to offer a superior light output, the Sirius offers the latest Samsung LED technology, has a diffused cover to mimic the appearance of halogen cabinet lights, and has no visible LED points. Sirius also has a 120 degree beam angle, which fills cabinets or work surfaces, and eliminates dark spots.

TECHNICAL INFO

Finish Chrome* or Brushed Nickel

Power Supply 12Vdc Cable Length 2m

Colour Appearance Warm White** or Natural White

Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 2.6W IP Rating IP44

Colour Rendering Index WW - Ra 82, NW - Ra 87
Total Lumens WW - 177lm NW - 157lm

Beam Angle 120°



COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights) SY9980B 15W 12Vdc LED Power Converter (1-5 lights) SY9739B 20W 12Vdc LED Power Converter (1-6 lights) SY7350C

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 1142m (SY7183) or 5m (SY7183/5) Extension Cable

*Recessed/Surface only

**Warm white only available in brushed nickel




DESIGNER TRI-LIGHT

PART CODE & DESCRIPTION

Sirius LED Designer Tri-Light Warm/Natural White

SY7464WW or NW






TRI-LIGHT

PART CODE & DESCRIPTION

Sirius LED Tri-Light
Warm/Natural White

SY7472WW or NW






DESIGNER RECTI-LIGHT

PART CODE & DESCRIPTION

Sirius LED Designer Recti-Light Warm/Natural White

SY7881WW or NW





RECESSED

PART CODE & DESCRIPTION

Sirius LED Recessed Brushed Nickel

Warm* or Natural White


Sirius LED Recessed Chrome

Natural White

SY7453A/BNWW or NW

SY7453CC/NW

*Warm white only available in brushed nickel







PART CODE & DESCRIPTION

Sirius LED Rec/Sur Brushed Nickel Warm* or Natural White

SY7462/BNWW or NW

Sirius LED Recessed/Surface Chrome/Natural White

SY7462CC/NW

*Warm white only available in brushed nickel



Spacer depth

SIRIUS TUNABLE



DIFFUSED LED CABINET LIGHT



Tunable white enables the user to choose their desired colour temperature, from warm white (2700K) to natural white (4000K) and to cool white (6000K) by simply using a hand held remote control, a smart phone or tablet using a free app (receiver features built in Wi-Fi capabilities) or via a wireless wall plate.

*Kits include 15W power converter, 3 way distribution cable & receiver. Please note the maximum number of lights that can be run per distributor cable is 3. Up to 5 lights can be run from the 15W driver, extra 3 way distribution cable required. Remote control required, sold separate.

TECHNICAL INFO

Finish Brushed Nickel

Power Supply 12Vdc Cable Length 2m

Colour Appearance Tunable White (Warm/Natural/Cool)
Colour Temperature Tunable White (3000K/4000K/6000K)

Wattage 2.6W
IP Rating IP44
Colour Rendering Index Ra 89
Total Lumens 158Im
Beam Angle 120°






CONTROL OPTIONS

(a) Tunable White Remote ControlSY9565(b) Additional Tunable White Receiver (Wi-Fi Series)SY7699B(c) Wall Mounted ControlSY8810/TUN



(d) 3 Way Distribution Cable SY7893A

(e) 2m Extension Cable (From 3 way splitter to lights) SY8018 2m (SY7183) or 5m (SY7183/5) Extension Cable (driver to receiver)






DESIGNER TRI-LIGHT

PART CODE & DESCRIPTION

Sirius Designer Tri-Light 2 Light Kit SY7939BTW/2

Sirius Designer Tri-Light 3 Light Kit SY7939BTW/3

Sirius Designer Tri-Light individual Light SY7938TW






TRI-LIGHT

PART CODE & DESCRIPTION

Sirius Tri-Light 2 Light Kit SY7941BTW/2 Sirius Tri-Light 3 Light Kit SY7941BTW/3

Sirius Tri-Light individual Light SY7940TW






DESIGNER RECTHIGHT

PART CODE & DESCRIPTION

Sirius Designer Recti 2 Light Kit SY7943BTW/2 Sirius Designer Recti 3 Light Kit SY7943BTW/3

Sirius Designer Recti individual Light

SY7942TW





RECESSED/SURFACE


PART CODE & DESCRIPTION

Sirius Recessed/Surface 2 Light Kit SY7937BTW/2

Sirius Recessed/Surface 3 Light Kit SY7937BTW/3

Sirius Recessed/Surface individual Light

SY7936TW



*Kits include 15W power converter, 3 way distribution cable & receiver. Remote control purchased separately

SIRIUS CONNECT



DIFFUSED LED CABINET LIGHT



The Sirius Connect features an innovative new plug and play system, in which the cable detaches directly from the back of the light unit enabling the fitting to be installed easily into the base of a cabinet. The Sirius Connect also features a diffused cover, so there are no visible LED points in the fitting, and also has a 120 degree beam angle which fills cabinets or work surfaces, eliminating dark spots.

TECHNICAL INFO

Finish Brushed Nickel

Power Supply 12Vdc Cable Length 2m

Colour Appearance Warm, Natural or Cool White
Colour Temperature 3000K - 3500K, 4000K - 4500K or

6000K -6500K

Wattage 2.6W IP Rating IP44

Colour Rendering Index WW - Ra 82, NW - Ra 85,

CW - Ra 86

Total Lumens WW - 177lm NW - 187lm

CW - 1771m

Beam Angle 120°



COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights)SY9980B15W 12Vdc LED Power Converter (1-5 lights)SY9739B20W 12Vdc LED Power Converter (1-6 lights)SY7350C

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming) Page 22/23
Wi-Fi 4 Zone Controls Page 24/25
Sensors, Switches & Dimmers Page 111 - 114
2m (SY7183) or 5m (SY7183/5) Extension Cable






DESIGNER TRI-LIGHT

PART CODE & DESCRIPTION

Sirius Connect LED Designer Tri-Light Warm/Natural/Cool White

SY9568WW/NW/CW






TRI-LIGHT

PART CODE & DESCRIPTION

Sirius Connect LED Tri-Light Warm/Natural/Cool White

SY9569WW/NW/CW






DESIGNER RECTI-LIGHT

PART CODE & DESCRIPTION

Sirius Connect LED Designer Recti-Light Warm/Natural/Cool White

SY7882WW/NW/CW






RECESSED

PART CODE & DESCRIPTION

Sirius Connect LED Recessed Warm/Natural/Cool White

SY9566WW/NW/CW





RECESSED/SURFACE

PART CODE & DESCRIPTION

Sirius Connect LED Recessed/Surface Warm/Natural/Cool White

SY9567WW/NW/CW



POLARIS CONNECT (ELK IN CARD A PONS



COB LED CABINET LIGHT



The Polaris COB Connect features an innovative new plug and play system, in which the cable detaches directly from the back of the light unit enabling the fitting to be installed easily into the base of a cabinet. This IP44 rated fitting is of die cast construction which ensures excellent heat sink, and the high quality lens intensifies the lumen output to provide market leading luminous efficacy from an LED cabinet light.

TECHNICAL INFO

Finish Brushed Nickel

12Vdc **Power Supply** Cable Length 1.5m

Natural White (4000 - 4500K) Colour Temperature

Wattage 3.4W IP44 IP Rating Ra 85 Colour Rendering Index Total Lumens 238lm Beam Angle 45°



COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-2 lights) SY9980B 15W 12Vdc LED Power Converter (1-4 lights) SY9739B 20W 12Vdc LED Power Converter (1-5 lights) SY7350C 30W 12Vdc LED Power Converter (1-6 lights) SY7715A

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming) Page 22/23 Wi-Fi 4 Zone Controls Page 24/25 Sensors, Switches & Dimmers Page 111 - 114 2m (SY7183) or 5m (SY7183/5) Extension Cable






DESIGNER TRI-LIGHT

PART CODE & DESCRIPTION

Polaris COB Connect LED Designer Tri-Light Natural White

SY7951BN/NW






TRI-LIGHT

PART CODE & DESCRIPTION

Polaris COB Connect LED Tri-Light Natural White

SY7953BN/NW






DESIGNER RECTI-LIGHT

PART CODE & DESCRIPTION

Polaris COB Connect LED Designer Recti-Light Recti-Light/Natural White

SY7952BN/NW





RECESSED

PART CODE & DESCRIPTION

Polaris COB Connect LED Recessed Natural White

SY7949BN/NW





RECESSED/SURFACE

PART CODE & DESCRIPTION

Polaris COB Connect LED Recessed/Surface Natural White

SY7950BN/NW





HALO

MULTI POINT LED CABINET LIGHT



The Halo collection features a stunning halo effect through various different fitting designs, which is available in natural white LED, with natural white halo.

TECHNICAL INFO

Finish Brushed Nickel

Power Supply 12Vdc

Cable Length 2m

Colour Appearance Natural White
Colour Temperature 4000K - 4500K

Wattage 3W
IP Rating IP44
Colour Rendering Index Ra 86
Total Lumens 232Im
Beam Angle 50°



COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-2 lights) SY9980B 15W 12Vdc LED Power Converter (1-5 lights) SY9739B 20W 12Vdc LED Power Converter (1-6 lights) SY7350C

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 1142m (SY7183) or 5m (SY7183/5) Extension Cable




DESIGNER TRI-LIGHT

PART CODE & DESCRIPTION

Halo LED Designer Tri-Light
Brushed Nickel/Natural White

SY7272NW/NW






TRI-LIGHT

PART CODE & DESCRIPTION

Halo LED Tri-Light
Brushed Nickel/Natural White

SY7273NW/NW






RECESSED

PART CODE & DESCRIPTION

Halo LED Recessed
Brushed Nickel/Natural White

SY7270NW/NW





RECESSED/SURFACE

PART CODE & DESCRIPTION

Halo LED Recessed/Surface Brushed Nickel/Natural White

SY7271NW/NW



CAPELLA 240V



LED CABINET LIGHT



This range of 240V cabinet lighting is a more discreet version of other larger mains voltage lights currently available. With the same visible appearance and size as our Sirius 12Vdc cabinet light range, this is a great option for any application requiring lighting without a power converter. This range also uses a simple to install plug in connector system.

PART CODE & DESCRIPTION

Capella Recessed Warm or Natural White SY7750BN/WW or NW

Capella Recessed/Surface
Warm or Natural White SY7751BN/WW or NW

No Power Converter Required

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (not dimmable)

Page 22/23

(a) Capella 2 Distribution Block

SY7754

(b) Capella 6 Way Distribution Block

SY7753

TECHNICAL INFO

Finish Brushed Nickel

Power Supply 240V Cable Length 1.5m

Colour Appearance Warm White or Natural White
Colour Temperature 3000K - 3500K or 4000K - 4500K


 Wattage
 2.6W


 IP Rating
 IP20

Colour Rendering Index WW - Ra 82 NW - Ra 87
Total Lumens WW - 1821m NW - 1941m

Beam Angle 100°








CAPELLA 240V



LED TRI-LIGHT



This 240V LED Tri-light is a discreet version of other larger mains voltage lights currently available. With the same visible appearance and size as our Sirius 12Vdc cabinet light range, this is a great option for any application requiring lighting without a power converter. This range also uses a simple to install plug in connector system.

PART CODE & DESCRIPTION

Capella Tri-Light
Warm or Natural White SY7752WW or NW

No Power Converter Required

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (not dimmable)

(a) Capella 2 Distribution Block

(b) Capella 6 Way Distribution Block

SY7753

TECHNICAL INFO


Beam Angle

Finish Brushed Nickel 240V **Power Supply** Cable Length 1.5m Colour Appearance Warm White or Natural White Colour Temperature 3000K - 3500K or 4000K - 4500K 2.6W Wattage IP20 IP Rating Colour Rendering Index WW - Ra 82 NW - Ra 87 Total Lumens WW - 182lm NW - 194lm

100°








SIRIUS TRICOLOUR



240V LINK LIGHT



The new LED link lights feature a built in switch to change the colour from warm white, to natural white and to cool white to suit decor or individual preference. The fittings are individually switched and fully linkable for ease of use, and can be butt jointed to make longer lengths if desired. 1.8m mains cable also included.

PART CODE & DESCRIPTION

222mm 3W LED Link Light	SY7690 TRICOLOUR
343mm 4W LED Link Light	SY7691 TRICOLOUR
525mm 8.4W LED Link Light	SY7692 TRICOLOUR
640mm 10W LED Link Light	SY7693 TRICOLOUR

No Power Converter Required

TECHNICAL INFO

Finish	White
Power Supply	240V
Cable Length	1.8m
Colour Appearance	Tricolour (3000K/4000K/6000K)
Colour Temperature	Tricolour (Warm/Natural/Cool)
Wattage	3W/4W/8.4W/10W
IP Rating	IP20
Colour Rendering Index (Based on 10W Link Light)	WW - Ra 83, NW - Ra 88, CW - Ra 88
Total Lumens (Based on 10W Link Light)	WW - 977lm, NW - 1098lm, CW - 1019lm


222/343/525/640mm 23mm

COMPATIBLE ACCESSORIES

JOIVIPATIBLE ACCESSORIES		
SY9553A		
SY7496		
SY9324		
SY9556		
SY9325		



SIRIUS 240V LINK LIGHT



The Sirius LED link lights come complete with a diffused cover and have no visible LED points which provides a wide flood of light. The fittings are individually switched and fully linkable for ease of use, and can be butt jointed to make longer lengths if desired. 1.8m mains cable also included.

PART CODE & DESCRIPTION

222mm 3W LED Link Light Warm White SY7690A/WW SY7690NW/1.8M 222mm 3W LED Link Light Natural White 343mm 4W LED Link Light Warm White SY7691A/WW 343mm 4W LED Link Light Natural White SY7691NW/1.8M 525mm 8.4W LED Link Light Warm White SY7692A/WW SY7692NW/1.8M 525mm 8.4W LED Link Light Natural White SY7693A/WW 640mm 10W LED Link Light Warm White 640mm 10W LED Link Light Natural White SY7693NW/1.8M 904mm 12W LED Link Light Warm White SY7694A/WW 904mm 12W LED Link Light Natural White SY7694NW/1.8M

No Power Converter Required



TECHNICAL INFO


Finish	White
Power Supply	240V
Cable Length	1.8m
Colour Appearance	Warm White or Natural White
Colour Temperature	3000K - 3500K or 4000K - 4500K
Wattage	3W/4W/8.4W/10W/12W
IP Rating	IP20
Colour Rendering Index (Based on 10W Link Light)	WW - Ra 83, NW - Ra 88
Total Lumens (Based on 10W Link Light)	WW - 907lm, NW - 927lm

COMPATIBLE ACCESSORIES

CELK PAR POHS

TUNABLE COB

LED FLEXIBLE STRIP 5m REEL



Tunable white enables the user to choose their desired colour temperature, from warm white (2700k) to natural white (4000k) to cool white (6000k) by simply using a hand held remote control, the wall mounted controller, or from a smart-phone or tablet using a free downloadable App. This product also utilises smooth dimming technology, so the unit can be set to totally suit customer requirements. Power converter, remote control & receiver required, purchased separate. Receiver features built in Wi-Fi capabilities.

The high output COB LED strip features LED points within close proximity to each other, creating a uniform light output with no spotting, perfect for illuminating handle-less kitchen designs. The strip has a depth of only 2mm so is ideal for situating underneath a worktop, and is suitable for installation on all coloured handle-less profiles without the need for an aluminium extrusion

This COB LED strip is supplied with very high bond (VHB) 3M tape.

PART CODE & DESCRIPTION

Tunable COB 5m Reel	SY2450
Accessories	
Remote Control & Receiver Kit (Wi-Fi Series)	SY5699B
Receiver (Wi-Fi Series)	SY7699B
Wall Mounted Control	SY8810/TUN
2m Reconnection Distribution Cable	SY2454
30mm Corner Connector (Flexi)	SY2456
Direct Connector	SY2452
Additional 3 Way Distributor Cable	SY7893A
2m Extension Cable	SY8018

TECHNICAL INFO

Power Supply	12Vdc
Adhesive	3M VHB

Cable Length 2m at both ends

Colour Temperature Tunable White (3000K/4000K/6000K)

Cut Marks Every 21mm


LEDs per metre 576

COMPATIBLE POWER CONVERTERS

50W 12Vdc LED Power Converter (max 4m) SY7351D 100W 12Vdc LED Power Converter (max 8m) SY7440A



RGB COB LED FLEXIBLE STRIP 5m REEL



RGB colour changing strip enables the user to choose from a wide variety of colours by simply using a hand held remote control, the wall mounted controller, or from a smart-phone or tablet using a free downloadable App. This product also utilises smooth dimming technology, so the unit can be set to totally suit customer requirements. Power converter, remote control & receiver required, purchased separate. Receiver features built in Wi-Fi capabilities.

The LED strip is supplied with very high bond (VHB) tape. Please note that the strip must be installed onto a clean, dry surface. Various extrusions are available for our LED strip, see page 64.

PART CODE & DESCRIPTION

RGB COB 5m Reel	SY2451
Accessories	
Remote Control & Receiver Kit (Wi-Fi Series)	SY7598B/WH*
Additional Receiver (Wi-Fi Series)	SY7538B
Wall Mounted Control	SY8810/RGB
2m Reconnection Distribution Cable	SY2453
30mm Corner Connector (Flexi)	SY2455
Direct Connector	SY2452
100mm Bridge Cable	SY7341A
1m Bridge Cable	SY7343A
5m Bridge Cable	SY7345A
Y-Splitter	SY7347A

^{*}Remote control also available in black please use code SY7598B/BL

TECHNICAL INFO

Power Supply 12Vdc Adhesive 3M VHB

Cable Length2m at both endsColour TemperatureRGB Colour Changing


Wattage 10W/m IP Rating IP20

Cut Marks Every 24mm

LEDs per metre 756


COMPATIBLE POWER CONVERTERS

50W 12Vdc LED Power Converter (max 5m) SY7351D 100W 12Vdc LED Power Converter (max 10m) SY7440A



COB SUPERIOR

LED FLEXIBLE STRIP 5m REEL



This high output COB LED strip features LED points within close proximity to each other, creating a uniform light output with no spotting, perfect for illuminating handle-less kitchen designs. The strip has a depth of only 1.7mm so is ideal for situating underneath a worktop, and is suitable for installation on all coloured handle-less profiles without the need for an aluminium extrusion. This LED strip also comes with VHB (Very High Bond) tape.

PART CODE & DESCRIPTION

Superior COB 5m Reel Warm or Natural White	SY9001WW or NW	
Accessories		
(a) Clamp on Distributor Cable	SY9044	
(b) Direct Connector	SY9023	
(c) Corner Connector (30mm Flexi)	SY9024	
(d) Corner Connector (Fixed)	SY9025	
Aluminium Extrusions	Page 64	
Kinetic Wireless Switching (inc. dimming)	Page 22/23	
Wi-Fi 4 Zone Controls	Page 24/25	
Sensors, Switches & Dimmers	Page 111 - 114	
2m (SY7183) or 5m (SY7183/5) Extension Cable		

(a) (b) (c) (d)

TECHNICAL INFO

Power Supply

LEDs per metre


Adhesive	3M VHB
Cable Length	2m at both ends
Colour Appearance	Warm White or Natural White
Colour Temperature	3000K - 3500K or 4000K - 4500K
Colour Rendering Index	> Ra 90
Wattage	4W/m
IP Rating	IP20
Cut Marks	Every 25mm

12Vdc

COMPATIBLE POWER CONVERTERS

15W 12Vdc LED Power Converter (up to 3m) SY9739B
 20W 12Vdc LED Power Converter (up to 5m) SY7350C
 30W 12Vdc LED Power Converter (up to 7m) SY7715A

512



COB STANDARD

CER POHS

LED FLEXIBLE STRIP 3/5m REEL



This COB LED strip features LED points within close proximity to each other, creating a uniform light output with no spotting, perfect for illuminating handle-less kitchen designs. The strip has a depth of only 1.7mm so is ideal for situating underneath a worktop, and is suitable for installation on all coloured handle-less profiles without the need for an aluminium extrusion. This LED strip also comes with VHB (Very High Bond) tape.

PART CODE & DESCRIPTION

Standard COB 3m Reel SY9022A/WW or NW Warm or Natural White

Standard COB 5m Reel SY9018WW or NW Warm or Natural White

Accessories

(a) Clamp on Distributor Cable SY9044

(b) Direct Connector SY9023

(c) Corner Connector (30mm Flexi) SY9024

(d) Corner Connector (Fixed) SY9025

Aluminium Extrusions Page 64

Kinetic Wireless Switch (inc. dimming) Page 22/23

Wi-Fi 4 Zone Controls Page 24/25

Sensors, Switches & Dimmers Page 111 - 114

2m (SY7183) or 5m (SY7183/5) Extension Cable

TECHNICAL INFO

Power Supply 12Vdc Adhesive 3M VHB

Cable Length 1.5m at both ends

Colour Appearance Warm White or Natural White

Colour Temperature 3000K - 3500K or 4000K - 4500K

Colour Rendering Index> Ra 90Wattage4W/mIP RatingIP20

Cut Marks Every 25mm

LEDs per metre 320

COMPATIBLE POWER CONVERTERS

15W 12Vdc LED Power Converter (up to 3m) SY9739B
 20W 12Vdc LED Power Converter (up to 5m) SY7350C
 30W 12Vdc LED Power Converter (up to 7m) SY7715A














IP67 LED FLEXIBLE STRIP 5m REEL



The new super-slim ARC LED strip offers a discreet, dot-less uniform light line. It can be recessed or surface mounted into or under cabinets or cupboards, alcoves or wall features using the 3M VHB adhesive tape which is applied to each 5 metre length of strip.

The super-slim ARC can negotiate 90 degree internal and external corners without creating any dark spots, and at 1.5w per metre, it is very energy efficient.

The product also comes with a 5-year warranty and is IP67 rated so it is totally waterproof.

PART CODE & DESCRIPTION

5m ARC Reel Warm or Natural White SY9026WW or NW

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (runs up to 5m) SY9980B 15W 12Vdc LED Power Converter (runs up to 10m) SY9739B

TECHNICAL INFO

Power Supply 12Vdc
Adhesive 3M VHB

Cable Length 2m at both ends

Colour Appearance Warm White or Natural White
Colour Temperature 3000K - 3500K or 4000K - 4500K

Colour Rendering Index> Ra 90Wattage1.5W/mIP RatingIP67

Cut Marks Every 25mm

LEDs per metre 60

COMPATIBLE ACCESSORIES

Aluminium Extrusions Page 64
Kinetic Wireless Switching (inc. dimming) Page 22/23
Wi-Fi 4 Zone Controls Page 24/25
Sensors, Switches & Dimmers Page 111-114

(EUK P W ROHS

FIFXIIF

IP44 LED FLEXIBLE LED STRIP 3m REEL



The clever design of the FLEXile LED strip allows it to bend around tight curves whilst offering illumination to both vertical and horizontal planes, perfect for illuminating curved units or islands. The strip offers a solid colour with no visible LED points, and has IP44 rating.

The accessory pack (SY8930A) includes mounting clips, screws and end caps. End caps must be applied to any cut end to maintain the IP rating of the strip.

PART CODE & DESCRIPTION

3m Kit

Warm, Natural or Cool White SY8931A/WW, NW or CW

Kit above includes 3M LED Strip, 1 x 30W power converter (max 3m), & 1 x accessory pack

3m Strip Warm White SY8913A 3m Strip Natural White SY8914A 3m Strip Cool White SY8915A

COMPATIBLE POWER CONVERTERS

20W 12Vdc LED Power Converter (runs up to 2m) SY7350C 30W 12Vdc LED Power Converter (runs up to 3m) SY7715A 50W 12Vdc LED Power Converter (runs up to 5m) SY7351D 100W 12Vdc LED Power Converter (runs up to 10m) SY7440A

TECHNICAL INFO

12Vdc **Power Supply**

Cable Length 1.5m at both ends

Colour Appearance Warm, Natural or Cool White Colour Temperature 3000K - 3500K, 4000K - 4500K or

6000K - 6500K

Colour Rendering Index WW - Ra 84, NW - Ra 87, CW - 87

Wattage 10W/m IP Rating IP44

Cut Marks Every 20mm

LEDs per metre 140

COMPATIBLE ACCESSORIES

Accessory Pack SY8930A Aluminium Extrusions Page 64 Kinetic Wireless Switching (inc. dimming) Page 22/23 Wi-Fi 4 Zone Controls Page 24/25 Sensors, Switches & Dimmers Page 111 - 114



FLEXIBLE LED STRIP







IP20 LED FLEXIBLE STRIP REELS







TECHNICAL INFO

Power Supply 12Vdc

Adhesive 3MVHI

 Cable Length
 2m at both ends

 Colour Temperature
 Warm 3000K - 3500K

Natural 4000K - 4500K

Wattage 4W/m

Cut Marks Every 50mm

LEDs per metre

TECHNICAL INFO

Power Supply 12Vdc

Adhesive 3MVF

Cable Length 2m at both ends

Colour Temperature Warm 3000K - 3500K

CRI WW - Ra 85 NW - Ra

Wattage 4W/
IP Rating IP20

Cut Marks Every 25mm

LEDs per metre 120

TECHNICAL INFO

Power Supply 12Vdc Adhesive 3MVH

Cable Length 2m at both ends

Colour Temperature Warm 3000K - 3500K Natural 4000K - 4500

CRI WW - Ra 82 NW -

Vattage 9.6W/m PRating IP20

Cut Marks Every 25mm

LEDs per metre 120







PART CODE & DESCRIPTION

5m Reel SY8982WW/NW

PART CODE & DESCRIPTION

5m Reel SY8976WW or NW

PART CODE & DESCRIPTION

 3M Reel
 SY8888NW or NW

 5m Reel
 SY8981WW or NW

COMPATIBLE POWER CONVERTERS

 15W 12Vdc (up to 3m)
 SY9739B

 20W 12Vdc (up to 5m)
 SY7350C

 30W 12Vdc (up to 7m)
 SY7715A

COMPATIBLE POWER CONVERTERS

 15W 12Vdc (up to 3m)
 SY9739B

 20W 12Vdc (up to 5m)
 SY7350C

 30W 12Vdc (up to 7m)
 SY7715A

COMPATIBLE POWER CONVERTERS

 20W 12Vdc (up to 2m)
 SY7350C

 30W 12Vdc (up to 3m)
 SY7715A

 50W 12Vdc (up to 5m)
 SY7351D

COMPATIBLE ACCESSORIES

Aluminium Extrusions
Page 64
(d) Corner Connector (Fixed)
SY9024
Kinetic Wireless Switching (inc. dimming)
Page 22/23
Wi-Fi 4 Zone Controls
Page 24/25
Sensors, Switches & Dimmers
Page 111 - 114
(d) Clamp on Distributor Cable
SY9044
(d) Corner Connector (Fixed)
SY9024
2m (SY7183) or 5m (SY7183/5) Extension Cable
(G) Clamp on Distributor Cable
SY9044
(G) Clamp on Distributor Cable

(a) Clamp on Distributor Cable SY9044 (a) (b) (c) (d)
(b) Direct Connector SY9023
(c) Corner Connector (30mm Flexi) SY9024

FLEXIBLE LED STRIP






IP65 LED FLEXIBLE STRIP 1, 2 & 3m LENGTHS







TECHNICAL INFO

Power Supply 12Vdc
Adhesive 3M

Cable Length Purchased separate

Colour Temperature

Warm 3000K - 3500K Natural 4000K - 4500k

WW/NW- Ra 85

C.W - Ra 87

Wattage 3.6W/n

IP Rating IP65

Cut Marks Every 62mn

EDs per metre 60

TECHNICAL INFO

Power Supply 12Vdc
Adhesive 3MVHE

Cable Length 1.5m at one end

Colour Temperature Warm 3000K - 3500k

CRI WW/NW - Ra 8

Wallage 4W/ IP Rating IP65

Cut Marks Every 50mm

Ds per metre

TECHNICAL INFO

Power Supply 12Vdc Adhesive 3MVHE

Cable Length 1.5m at one end

Colour Temperature Warm 3000K - 3500K

CRI WW - Ra 85 N

Wattage 9.6W/m

IP Rating IP65

Cut Marks Every 25mm

LEDs per metre 120







PART CODE & DESCRIPTION

1m Length SY7759WW, NW or CW2m Length SY7760WW, NW or CW3m Length SY7761WW, NW or CW

Distribution Cable SY7758A

Corner Connector SY7912

Straight Connector SY7913

PART CODE & DESCRIPTION

1m Length SY8983WW or NW2m Length SY8984WW or NW3m Length SY8985WW or NW

PART CODE & DESCRIPTION

 1m Length
 SY8986WW or NW

 2m Length
 SY8987WW or NW

 3m Length
 SY8988WW or NW

COMPATIBLE POWER CONVERTERS

1

7

 15W 12Vdc (up to 4m)
 SY9739B

 20W 12Vdc (up to 5m)
 SY7350C

 30W 12Vdc (up to 8m)
 SY7715A

COMPATIBLE POWER CONVERTERS

 15W 12Vdc (up to 3m)
 SY9739B

 20W 12Vdc (up to 5m)
 SY7350C

 30W 12Vdc (up to 7m)
 SY7715A

COMPATIBLE POWER CONVERTERS

20W 12Vdc (up to 2m) SY7350C 30W 12Vdc (up to 3m) SY7715A 50W 12Vdc (up to 5m) SY7351D

COMPATIBLE ACCESSORIES

Aluminium Extrusions Page 64 Sensors, Switches & Dimmers Page 111 - 114
Kinetic Wireless Switching (inc. dimming) Page 22/23 2m (SY7183) or 5m (SY7183/5) Extension Cable
Wi-Fi 4 Zone Controls Page 24/25

ALUMINIUM EXTRUSIONS

FOR LED STRIP

Mounting LED strip within an extrusion not only helps to keep runs straight and neat, it also assists with heat dissipation, therefore prolonging the life of the LED strip. A diffuser finishes off the clean look, and provides protection from dust and water splashes. We have various styles available depending on the application.



1m Shallow Surface Mounted Extrusion Aluminium SY9573/1 2m Shallow Surface Mounted Extrusion Aluminium SY9573/2




















BESPOKE LIGHTING STRIPS

Bespoke cut lengths of LED strip within aluminium extrusions offers a fast fit solution without the need for cutting strip and the profile to sui on site.

Numerous types of recessed or surface mounted profiles are available, along with colour temperature from 2500K up to 6500K

All products are plug & play and we can also supply various door sensors & PIR sensors







Our Bespoke Lighting Collection has been designed to offer a bespoke solution for lighting & lighting controls within kitchens, bedrooms, bathrooms, outdoor kitchens & home offices.

A project manager is assigned to all installations, and they are available to assist with advice, site visits, before, during and after the installation of our products.

Our technical & design team can offer assistance from concept to completion on all projects and are on hand to discuss subjects such as photometric data, lux levels and wiring configurations.

All the lighting is compatible with home automation systems such as Lutron & Rako.

Please contact our technical team on 0113 286 6686 or email tech@sycamoreled.com to find out more.















ALL PRODUCTS ARE COVERED BY A 5-YEAR WARRANTY

Excludes battery operated products, power converters, accessories, pendants & motorised pop ups

NOVA PRO



RECHARGEABLE LITHIUM BATTERY SENSOR LIGHT



The Nova Pro lithium battery light is perfect for situating within cabinets, cupboards or drawers. The unit features a integrated PIR sensor, to automatically turn the light on when movement is sensed within a 4 metre range. When no further movement is detected after 20 seconds, the unit will turn itself off.

It features a slim, discreet profile, with a diffused natural white LED illuminated panel. It is also easily removed from its magnetic brackets for charging. USB-C charging cable included

The battery light will last for one month based on 5 minutes use per day, and takes 2.5 hours to charge from empty to fully charged.

PART CODE & DESCRIPTION

Nova Pro 205mm	SY9039
Nova Pro 305mm	SY9040
Nova Pro 405mm	SY9041
Nova Pro 505mm	SY9042

TECHNICAL INFO

Finish Silver
Lithium Battery 5V

Battery Capacity 600mAh - 2400mAh

Lighting Time1 Month (based on 5 minutes usage per day without charge)

Re-charge Time 2.5 hours from no charge to full

Charging Via USB cable (included)


Colour Appearance Natural White

Colour Appearance Natural White Colour Temperature 4000K - 4500K

PIR Sensor Max Distance 4m

Guarantee 12 Months





NOVA MULTI

RECHARGEABLE LITHIUM BATTERY SENSOR LIGHT





This battery light is multi-functional, meaning it can be used as a door sensor, or a swipe sensor by choosing your preference using the switch on the front of the unit.

It features a diffused natural white LED illuminated panel, and is also easily removed from its magnetic fixing pads for charging. USB charging cable included.

With its lightweight magnetic design it can be retrofit into kitchen drawers or cupboards with ease.

PART CODE & DESCRIPTION

Nova Multi 200mm

SY8979

TECHNICAL INFO

Finish Silver
Lithium Battery 5V

Battery Capacity 600mAh

Lighting Time1 Month (based on 5 minutes usage per day without charge)

Re-charge Time 2 hours from no charge to full

Charging Via USB cable (included)

Colour Appearance Natural White

Colour Temperature 4000K - 4500K

PIR Sensor Max Distance 4cm

Guarantee 12 Months



VEGA ROUND



LED PLINTH LIGHT



This recessed plinth light adds great mood lighting into a kitchen. It features a diffused cover so the LED points are not visible. The sleek round design has a brushed nickel finish. Available in Warm White or Natural White.


PART CODE & DESCRIPTION

Vega Round 4 Light Plinth Kit Warm or Natural White

SY8975WW or NW

Power Converter Included





TECHNICAL INFO

Finish Brushed Nickel

Power Supply 12Vdc Cable Length 1.5m

Colour AppearanceWarm White or Natural WhiteColour Temperature3000K - 3500K or 4000K - 4500K

Wattage 1.2W IP Rating IP20

Colour Rendering Index WW - Ra 81 NW - Ra 85
Total Lumens WW - 45lm NW - 51lm

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

VEGA SQUARE



LED PLINTH LIGHT



The Vega recessed plinth light adds great mood lighting into a kitchen. It features a diffused cover so the LED points are not visible. The sleek square design has a brushed nickel finish, and is available in Warm White or Natural White.


PART CODE & DESCRIPTION

Vega Square 4 Light Plinth Kit Warm or Natural White

SY8974WW or NW

Power Converter Included





TECHNICAL INFO

Finish Brushed Nickel

Power Supply 12Vdc Cable Length 1.5m

Colour AppearanceWarm White or Natural WhiteColour Temperature3000K - 3500K or 4000K - 4500K

Wattage 1.2W IP Rating IP20

Colour Rendering Index WW - Ra 80 NW - Ra 85

Total Lumens WW - 54lm NW - 67lm

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

SIRIUS EYELID



LED PLINTH LIGHT




The Sirius Eyelid LED lights are a very unique set of plinth lights, which will add a stylish edge to a kitchen design. The Sirius Eyelid feature natural white LED with a stainless steel finish and are available in a four light pack, which also includes the power converter to run them. Can be recessed or surface mounted with the spacer included.

PART CODE & DESCRIPTION

Sirius Eyelid 4 Light Plinth Kit
Natural White SY7295BN

Power Converter Included





TECHNICAL INFO

Finish Stainless Steel 12Vdc **Power Supply** Cable Length 2m Colour Appearance Natural White Colour Temperature 4000K - 4500K 1W Wattage IP Rating IP44 Colour Rendering Index Ra 84 Total Lumens 25lm

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

SIRIUS SQUARE

LED PLINTH LIGHT



The small square plinth light is part of our Sirius collection which features a diffused cover to hide the LED points within the fitting for a sleek look. The square plinth light is surface mounted, and is easily installed using the strong adhesive back included. The kit includes 3 lights & 1 power converter which can run a maximum of 4 lights.

PART CODE & DESCRIPTION

Sirius Square 3 Light Plinth Kit Warm or Natural White


SY7523WW or NW

Sirius Square Plinth Light Additional Warm or Natural White

SY7524WW or NW

Power Converter Included





TECHNICAL INFO

Finish Stainless Steel

Power Supply 12Vdc Cable Length 2m

Colour Appearance Warm White or Natural White

Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 1.5W IP Rating IP20

Colour Rendering Index WW - Ra 80 NW - Ra 86
Total Lumens WW - 73Im NW - 82Im

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

VERVE 15mm



LED PLINTH LIGHT



This small and discreet plinth light is available with either cool or warm white LED, giving a choice to suit any particular design. The 15mm plinth lights are available in a 4 or 10 light kit, which includes the power converter. Add on lights are also available, up to a maximum of 10 lights can be run per power converter.


PART CODE & DESCRIPTION

4 Light Kit (Stainless Steel) Warm/Cool SY9936WW or CW 10 Light Kit (Stainless Steel) Warm/Cool SY9928A/WW or CW Individual (Stainless Steel) Warm/Cool SY9937WW or CW

For black finish please purchase kit required from above, and purchase the covers separate, listed below.

Black Cover (individual) SY9939BK

Power Converter Included



TECHNICAL INFO

Finish Stainless Steel

Power Supply 12Vdc Cable Length 1.5m

Colour Appearance Warm White or Cool White
Colour Temperature 3000K - 3500K or 6000 - 6500k

Wattage 0.2W IP Rating IP67





COMPATIBLE ACCESSORIES

Sensors, Switches & Dimmers

Kinetic Wireless Switching (inc. dimming)

Wi-Fi 4 Zone Controls

Page 22/23 Page 24/25 Page 111 - 114

LED DRAWER LIGHT



WITH INTEGRATED SENSOR



This soft start LED drawer light has an integrated infra red sensor for ease of use, which switches the light on or off automatically when the drawer is opened or closed. Available in different lengths, the auto drawer light is ideal for illuminating pan drawers. The drawer is suitable for 15mm to 22mm carcass panels.

PART CODE & DESCRIPTION

360mm Auto LED Drawer Light 2.5W (for 400mm Cabinet Size)	SY8921
460mm Auto LED Drawer Light 3.2W (for 500mm Cabinet Size)	SY8922
560mm Auto LED Drawer Light 3.9W (for 600mm Cabinet Size)	SY8923
760mm Auto LED Drawer Light 5.3W (for 800mm Cabinet Size)	SY8924
860mm Auto LED Drawer Light 6W (for 900mm Cabinet Size)	SY8925
960mm Auto LED Drawer Light 6.7W (for 1000mm Cabinet Size)	SY8926

TECHNICAL INFO


Finish	Stainless Steel
Power Supply	12Vdc
Cable Length	1.5m
Colour Appearance	Natural White
Colour Temperature	4000K - 4500K
Colour Rendering Index	Ra 83
Wattage	As Listed
IP Rating	IP20

COMPATIBLE ACCESSORIES

2m (SY7183) or 5m (SY7183/5) Extension Cable

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (Max 8W) SY9980B 15W 12Vdc LED Power Converter (Max 15W) SY9739B 20W 12Vdc LED Power Converter (Max 20W) SY7350C





VEGA IP44 ILLUMINATED LED SHELF



This LED shelf features a stylish panel, with a natural white light emitted through the shelf from the LED situated within the aluminium. The shelf is easily installed using the hanging brackets supplied and is available in 400mm or 600mm lengths. The maximum load of the shelf is 3Kg and is suitable for installation in bathrooms zones 1 and 2.

PART CODE & DESCRIPTION

Vega IP44 Illuminated LED Shelf 400mmSY8939Vega IP44 Illuminated LED Shelf 600mmSY8940

No Power Converter Required

TECHNICAL INFO

Finish Aluminium

Power Supply 240V


Cable Length 2m

Colour Appearance Natural White

Colour Temperature 4000K - 4500K

Wattage 13W/16W

IP Rating IP44



SIRIUS 1P44 ILLUMINATED LED FLOATING SHELF





This LED shelf features a stylish opal acrylic panel, with a natural white glow emitted through the shelf from the LED situated within the aluminium hanging bracket.

The shelf is easily installed using the included hanging brackets, and is available in 600mm or 900mm lengths. The maximum load the shelf can hold is 3 kilograms, and is suitable for installation in bathrooms zones 1 & 2.

PART CODE & DESCRIPTION

Sirius IP44 Illuminated LED Floating Shelf 600mm SY7417A Sirius IP44 Illuminated LED Floating Shelf 900mm SY7418A

No Power Converter Required

TECHNICAL INFO


Finish Aluminium

Power Supply 240V

Cable Length 2m

Colour Appearance Natural Wh

Colour Appearance Natural White
Colour Temperature 4000K - 4500K
Wattage 10W/15W
IP Rating IP44



SIRIUS LED GLASS SHELF LIGHT





This clever clip on LED can transform a normal glass shelf into an illuminated shelf with the clip on U shaped LED profiles. The clip on LED is 450mm in length, and fits 4mm or 6mm glass. The LED is available in natural white which suits either contemporary or traditional designs. The strip offers a solid colour with no visible LED points.

PART CODE & DESCRIPTION

Clip on LED for Glass Shelf 450mm

SV804

TECHNICAL INFO

Power Supply 12Vdc Cable Length 1.5m

Colour Appearance Natural White
Colour Temperature 4000K - 4500K

 Wattage
 2.5W

 IP Rating
 IP20

COMPATIBLE POWER CONVERTERS

8W 12Vdc LED Power Converter (1-3 lights)SY9980B15W 12Vdc LED Power Converter (1-5 lights)SY9739B20W 12Vdc LED Power Converter (1-6 lights)SY7350C

COMPATIBLE ACCESSORIES


Kinetic Wireless Switching (inc. dimming)

Wi-Fi 4 Zone Controls

Sensors, Switches & Dimmers

2m (SY7183) or 5m (SY7183/5) Extension Cable







With a contemporary matt white finish on the outside, the Parma White would look stunning over a breakfast bar or dining area. The interior features a built in natural white LED, surrounded by a stylish copper finish. The cable length is adjustable to suit different areas of a design as desired. This product is dimmable using a trailing edge dimmer switch or our Kinetic Smart Wireless control system. (Page 22/23).

PART CODE & DESCRIPTION

Parma White COB LED Pendant Natural White

SY7809WH

TECHNICAL INFO

Power Supply 240V

Dimensions H: 470 - 1870mm, Dia: 230mm Pendant H: 370mm

Colour Temp. Natural White

Wattage 8W

Finish Matt White/Copper



The stunning Parma Black LED pendant light is available with a matt black finish on the outer body, with an on-trend copper finish on the interior. The Parma pendant features a built in LED in a natural white colour temperature, and includes an adjustable cable to suit various areas of the kitchen or home. This product is dimmable using a trailing edge dimmer switch or our Kinetic Smart Wireless control system (Page 22/23).

PART CODE & DESCRIPTION

Parma Black COB LED Pendant Natural White

SY7809BL

TECHNICAL INFO

Power Supply 240V

Dimensions H: 470 - 1870mm, Dia: 230mm Pendant H: 370mm

Colour Temp. Natural White

Wattage 8W

Finish Matt Black/Copper



This stylish pendant is perfect for anyone wishing to infuse a minimalistic look into their designs and would be ideal for creating an industrial feel within the kitchen over an island or dining area.

PART CODE & DESCRIPTION

Concreto E27 Pendant

SY7812GW

TECHNICAL INFO

Power Supply 240V

Dimensions H: 400 - 1800mm, Dia: 140mm, Pendant H: 300mm Lamp Type E27 (Purchased separate, please see page 115)

Finish Concrete Effect



The Gabbia metal caged pendant brings a modern twist on vintage and industrial style lighting. Finished in polished copper plate, the design casts an interesting light pattern to your interior and works well with a LED filament bulb. With height adjustable cable.

PART CODE & DESCRIPTION

Gabbia E27 Pendant

SY72813

TECHNICAL INFO

Power Supply 240V

Dimensions H: 350 - 1550mm, Dia: 310mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Polished Copper Plate



The Harbour is a seven light globe pendant featuring simple classic stepped metalwork. The striking clear bubble effect glass shade contains faceted glass details for extra sparkle, alternatively these can be removed if you desire a more simple product look. Finished in chrome and suspended from height adjustable clear flex.

PART CODE & DESCRIPTION

Harbour 7 Light E14 Pendant

SY76292

TECHNICAL INFO

Dimensions H: 315 - 1440mm, Dia: 500mm

Lamp Type E14 (Purchased separate, please see page 115)

Finish Chrome with clear bubble glass



The Harbour is a timeless large globe pendant light featuring simple classic stepped metalwork. The striking clear bubble effect glass shade contains faceted glass details for extra sparkle, alternatively these can be removed if you desire a more simple product look. Finished in chrome and suspended from a height adjustable wire cable and clear flex.

PART CODE & DESCRIPTION

Harbour E27 Pendant

SY76381

TECHNICAL INFO

Power Supply 2

Dimensions H: 400 - 1600mm, Dia: 300mm, Pendant H: 365mm Lamp Type E27 (Purchased separate, please see page 115)

Finish Chrome with clear bubble glass

E27
Lamp
Required

A simple clear glass shade with a bubble effect to the glass. Complete with chrome adjustable cable set.

PART CODE & DESCRIPTION

Dimitri E27 Pendant

SY73974A

TECHNICAL INFO

Power Supply 240V

Dimensions H: 500 - 1800mm, Pendant H:200mm, Dia: 300mm Lamp Type E27 (Purchased separate, please see page 115)

Finish Clear bubble glass/Chrome

An angular glass pendant, finished with a antique brass trim. Complete with a black twisted adjustable flex with antique brass ceiling plate.



PART CODE & DESCRIPTION

Beaumont E27 Pendant

SY60892A

TECHNICAL INFO

Power Supply 240V

Dimensions H: 500 - 1840mm, Pendant H: 240mm, Dia: 155mm Lamp Type E27 (Purchased separate, please see page 115)

Finish Antique Brass



The Brydon ceiling pendant features a ribbed round glass shade hanging from a height adjustable decorative chain finished in antique brass.

PART CODE & DESCRIPTION

Brydon E27 Pendant

SY71123

TECHNICAL INFO

Power Supply 240V

Dimensions H: 400 - 1000mm, Dia: 250mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Antique Brass Plate & Clear Ribbed Glass



The Dickens is a stylish height adjustable pendant, finished in an on trend mix of two finishes; matt black and solid brass.

PART CODE & DESCRIPTION

Dickens E27 Pendant

SY69778

TECHNICAL INFO

Power Supply 240V

Dimensions H: 400 - 1400mm, Pendant H: 280mm, Dia: 216mm Lamp Type E27 (Purchased separate, please see page 115)

Finish Matt Black & Antique Brass



The Lambeth 1 light pendant has an adjustable drop and combines metal frame work with a satin nickel or antique brass finish and clear glass panels. for options).

PART CODE & DESCRIPTION

Lambeth E27 Pendant Satin Nickel SY70323

Lambeth E27 Pendant Antique Brass SY69454

TECHNICAL INFO

Power Supply 240V

Dimensions H: 500 - 1900mm

Pendant H: 377mm, Dia: 200mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Satin Nickel or Antique Brass



The Lambeth 4 light pendant has an adjustable drop and combines metal frame work with a satin nickel or antique brass finish and clear glass panels.

PART CODE & DESCRIPTION

Lambeth 4 Light E14 Pendant Satin NickelSY70324Lambeth 4 Light E14 Pendant Antique BrassSY69455

TECHNICAL INFO


Power Supply 240V

Dimensions H: 600 - 1980mm, Dia: 300mm

Lamp Type E14 (Purchased separate, please see page 115)

Finish Satin Nickel or Antique Brass















Create that cool urban look with this industrial six light pendant, simple in construction with smooth copper plated or matt black lamp holders suspended from height adjustable black fabric flex. Select the position of each lamp, able to reach over a large area of your interior for perfect illumination.

PART CODE & DESCRIPTION

Studio 6 Light E27 Pendant CopperSY76580Studio 6 Light E27 Pendant BlackSY76583

TECHNICAL INFO

Power Supply 240V

Dimensions H: 220 - 1620mm Dia: 150 - 3000mm

Lamp Type E27 (Purchased separate, please see page 115)
Finish Copper Plated or Matt Black with Black Flex

Create that cool urban look with this industrial three light pendant, simple in construction with smooth chrome plated lamp holders suspended from height adjustable black fabric flex. Select the position of each lamp, able to reach over a large area of your interior for perfect illumination.

PART CODE & DESCRIPTION

Studio 3 Light E27 Pendant Chrome

SY76576

TECHNICAL INFO

Power Supply 240V

Dimensions H: 220 - 1620mm, Dia: 150 - 3000mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Chrome with Black Flex

Create that cool urban look with this industrial pendant. Simple in construction with a single matt black painted lamp holder suspended from height adjustable black fabric flex.

PART CODE & DESCRIPTION

Studio E27 Pendant Matt Black

SY76581

TECHNICAL INFO

Power Supply 240V

Dimensions H: 220 - 1620mm, Dia: 100mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Matt Black with Black Flex

An on-tend vintage style cable set, chrome plated finish with authentic industrial knurled details, suspended from height adjustable fabric flex. The perfect carrier for filament LED lamps to create that 'resto' style exposed lamp look.

PART CODE & DESCRIPTION

Cambourne E27 Pendant Chrome (Black & White Flex) SY76584

Cambourne E27 Pendant Antique Brass (Black & Cream Flex) SY76585

TECHNICAL INFO

Power Supply 240V

Dimensions H: 230 - 1630mm, Dia: 100mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Chrome or Antique Brass

PENDAI LIGHTING



A captivating 'holographic' style light effect glass pendant, with chrome plated ceiling cover and height adjustable clear cable. Perfect for use with filament LED lamps.

PART CODE & DESCRIPTION

Stellar E27 Pendant


SV74939

TECHNICAL INFO

Power Supply

Dimensions H: 400 - 1300mm, Pendant H: 280mm, Dia: 220mm Lamp Type E27 (Purchased separate, please see page 115) Finish Chrome holographic glass & chrome plate





Delphine 3 Light E14 Pendant

SY76360

TECHNICAL INFO

Power Supply

Dimensions H: 505 - 1405mm, Dia: 450mm

Lamp Type E14 (Purchased separate, please see page 115)

Gold leaf

Finish

This metal caged shade finished in an antique copper effect plate puts a modern twist on vintage and industrial style lighting. Works well with a filament bulb. Height is adjustable at time of fitting.



PART CODE & DESCRIPTION

Nicole Round E27 Pendant

SV68987

TECHNICAL INFO

Power Supply

240V

Dimensions H: 450 - 1400mm, Dia: 300mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish

Antique Copper



A single ceiling pendant made from a cognac tinted, rippled glass. Supplied with a modern classic cable set, finished in an antique brass plate with a decorative black twisted adjustable flex.

PART CODE & DESCRIPTION

Eileen E27 Pendant

SY60298A

TECHNICAL INFO

Power Supply

Dimensions H: 500 - 1845mm, Dia: 220mm

Lamp Type E27 (Purchased separate, please see page 115) Finish

Cognac ripple glass shade



An impressive polished chrome finish 2 hoop LED pendant suspended from adjustable wire. Low maintenance costs and energy efficient with a 20.5W integrated warm white LED - (1740 lumens). Please note this pendant is not dimmable.

PART CODE & DESCRIPTION

Kline 2 Ring LED Pendant Warm White

SYKLINE-2CH

TECHNICAL INFO

Power Supply 240V

Dimensions H: 480 - 1250mm, Dia: 450mm

Colour Temperature Warm White LED (included) with built in LED driver

Wattage 20.5W

Finish Polished Chrome



Contemporary LED ceiling pendant with a striking continuous loop of LED lights. Perfect for modern interiors and finished in a luxurious gold leaf. Seemingly the pendant "floats", suspended from subtle clear cables that are height adjustable. The impressive loop design is an amazing centrepiece to any interior, creating an striking light effect. 33W warm white integrated LED - (1650 lumens). Please note this pendant is not dimmable.

PART CODE & DESCRIPTION

Scribble Ring LED Pendant Warm White

SY72479

TECHNICAL INFO

Power Supply 240V

Dimensions H: 480 - 1700mm, Dia: 550mm **Colour Temperature** Warm White LED with built in LED driver

Wattage 33W
Finish Gold Leaf



A bold and timeless bright nickel plated pendant with sand blasted glass diffuser and authentic classic detailing. Height adjustable cable.

PART CODE & DESCRIPTION

Fenton E27 Pendant

SY73103

TECHNICAL INFO

Power Supply 240V

Dimensions H: 700 - 1370mm, Dia: 370mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Bright Nickel



The height adjustable Hex pendant is on trend with its geometric, angular design and chrome effect or copper finish. Formed from a collection of mesh triangles, the cut outs create a fabulous light effect.

PART CODE & DESCRIPTION

Hex E27 Pendant ChromeSY72817Hex E27 Pendant CopperSY72815

TECHNICAL INFO

Power Supply 240V

Dimensions H: 450 - 1350mm, Dia: 320mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Chrome or Copper









The perfect 'must have' multi pendant light. The mixed plated finishes and open hoop design make this bang on-trend with a fun contemporary aesthetic, easily placeable in today's modern homes. Height adjustable to create a unique look. Pair with LED filament lamps to complete the look.

PART CODE & DESCRIPTION

Hoop 3 Light E27 Pendant

SY81922

TECHNICAL INFO

Power Supply 240V

Dimensions H: 700 - 1200mm, W: 388mm, D: 220mm

Lamp TypeE27 (Purchased separate, please see page 115)FinishBrushed Copper, Brushed Nickel & Brushed Brass

The perfect 'must have' single pendant light, bang on-trend with a fun contemporary aesthetic. Supplied with adjustable cable.

PART CODE & DESCRIPTION

Hoop E27 Pendant Brushed Copper

SY90456

TECHNICAL INFO

Power Supply 240V

Dimensions H: 300 - 1200mm, W: 250mm, D: 100mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Brushed Copper

This brushed brass single pendant light is bang on-trend with a fun contemporary aesthetic. Supplied with adjustable cable.

PART CODE & DESCRIPTION

Hoop E27 Pendant Brushed Brass

SY81921

TECHNICAL INFO

Power Supply 240\

Dimensions H: 300 - 1200mm, W: 250mm, D: 100mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Brushed Brass

The perfect 'must have' single pendant light, bang on-trend with a fun contemporary aesthetic. Supplied with adjustable cable.

PART CODE & DESCRIPTION

Hoop E27 Pendant Brushed Nickel

SY90454

TECHNICAL INFO

Power Supply 240V

Dimensions H: 300 - 1200mm, W: 250mm, D: 100mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Brushed Nickel

LIGHTING



An authentic 'resto' style industrial pendant, finished in antique brass or copper plating with authentic knurled lamp holder details and clear glass shades. Suspended from height adjustable black fabric flex, pair with filament LED lamps for that perfect industrial style. The perfect addition for today's stylish homes to create that on trend bar, bistro look.

PART CODE & DESCRIPTION

Hansen E27 Pendant Antique Brass SY77272 Hansen E27 Pendant Copper SY76332

TECHNICAL INFO

Power Supply 240V

Dimensions H: 400 - 1270mm, Pendant H: 225mm, Dia: 225mm Lamp Type E27 (Purchased separate, please see page 115)

Finish Antique Brass or Copper



A cool geometric shaped wire frame pendant light, in a matt black finish with smart satin gold painted detail. Creating amazing light patterns and suspended from height adjustable twisted black fabric flex, this cool pendant light is perfect for use with filament LED lamps.

PART CODE & DESCRIPTION

Deco E27 Pendant

SY76686

TECHNICAL INFO

Power Supply 240V

Dimensions H: 570 - 1470mm, Dia: 400mm, Pendant H: 445mm E27 (Purchased separate, please see page 115) Lamp Type Matt Black

Finish

The Lampada is an indoor ceiling pendant finished in satin nickel and glass. The cable has an adjustable drop.



PART CODE & DESCRIPTION

Lampada E27 Pendant

SY60799

TECHNICAL INFO

Power Supply 240V

Dimensions H: 400 - 1000mm, Dia: 330mm

E27 (Purchased separate, please see page 115) Lamp Type

Finish Satin Nickel



Following the 70's trend this Sputnik style pendant light is finished in satin gold finish. 9 lights are scattered among the metal spikes creating a stunning centrepiece. With height adjustable cable.

PART CODE & DESCRIPTION

Orta 9 Light G9 Pendant

SY70575

TECHNICAL INFO

Power Supply 240V

Dimensions H: 520 - 1900mm, Dia: 620mm

G9 (Purchased separate, please see page 115) Lamp Type

Finish Satin Brass



An angular cage pendant made from glass panels with an antique brass effect trim. Height adjustable antique brass chain with black fabric flex

PART CODE & DESCRIPTION

Avery E27 Pendant

SY73117

TECHNICAL INFO

Power Supply 240V

Dimensions H: 800 - 1650mm, Dia: 230mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Antique Brass

A glass pendant with a shiny copper plated exterior and a silver plated inner. Adjustable drop up to 1500mm.



PART CODE & DESCRIPTION

Rosa E27 Pendant

SY61705

TECHNICAL INFO

Power Supply 240

Dimensions H: 350 - 1500mm, Dia: 345mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Coppe



Elegantly curved LED pendant finished in a soft matt nickel effect plate. With natural white 18W integrated LED - 1480 lumens. Height adjustable black fabric flex. This product is dimmable using a trailing edge dimmer switch or our Kinetic Smart Wireless control system (see Page 22/23).

PART CODE & DESCRIPTION

Brosnan LED Pendant Natural White Matt Nickel

SY61296

Brosnan LED Pendant Natural White Antique Brass

SY61299

TECHNICAL INFO

Dimensions H: 300 - 1900mm, Dia: 300mm

Colour Temperature Natural White

Wattage 18V

Finish Matt Nickel or Antique Brass



This metal caged shade finished in an antique copper effect plate puts a modern twist on vintage and industrial style lighting. Works well with a filament bulb. Height is adjustable at time of fitting.

PART CODE & DESCRIPTION

Nicole E27 Pendant

SY68986

TECHNICAL INFO

Power Supply 240V

Dimensions H: 350 - 1300mm, Dia: 300mm

Lamp Type E27 (Purchased separate, please see page 115)

Finish Antique Copper

6W SWITCHABLE

DIMMABLE

<u>IP65 FIRE RATED DOWNLIGHT</u>
















Choose from 3000k, 4000k or 6000k by simply choosing your preference using the integrated switch on the front of the fitting. It is also fully dimmable from most standard wall dimmers, and also includes the power converter. The light output is equivalent to a 50W GU10 halogen lamp, but due to the latest LED technology it uses 85% less energy, helping to save money and the environment.

This ultra slim fitting is designed to allow loft insulation to be continuously run over the back of the fitting (IC Rated), and features a speed fit tool free loop in - loop out terminal. The colour appearance can be changed at any time without removing the fitting from the ceiling by simply removing the bezel.

TECHNICAL INFO

Power Supply 240V

Colour Appearance Switchable - Warm, Natural or

Cool

Colour Temperature Switchable - 3000K, 4000K or

6000K

Wattage 6W Beam Angle 40°

Total Lumens WW - 593lm NW - 680lm,

CW - 635lm

IP Rating IP65

Colour Rendering Index >Ra 80

Finish White (Chrome, Brushed Nickel,

& Matt Black available to purchase separate)

Cut Out Size 65mm

PART CODE & DESCRIPTION

6W Switchable Downlight White SY9050WH

ADDITIONAL BEZELS


Matt Black BezelSY9051BKChrome BezelSY9051CCBrushed Nickel BezelSY9051BN

Power Converter Included

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)

Page 22/23





8W SWITCHABLE

DIMMABLE

IP65 FIRE RATED DOWNLIGHT













Choose from 3000k, 4000k or 6000k by simply choosing your preference using the integrated switch on the fitting. It is also fully dimmable from most standard wall dimmers, and also includes a built-in power converter.

The light output is equivalent to a 50W GU10 halogen lamp, but due to the latest LED technology it uses 85% less energy, helping to save money and the environment.

The fitting is designed to allow loft insulation to be continuously run over the back of the fitting (IC Rated), and features a loop in - loop out clip block.

TECHNICAL INFO

Power Supply 240V

Colour Appearance Switchable - Warm, Natural or

Cool

Colour Temperature Switchable - 3000K, 4000K or

6000K

Wattage 8WBeam Angle 60°

Total Lumens WW - 782lm NW - 916lm, CW -

805lm

IP Rating IP65

Colour Rendering Index >Ra 80

Finish White (Chrome, Brushed Nickel,

Matt Black & Gold available to

purchase separate)

Cut Out Size 70mm

PART CODE & DESCRIPTION

8W Switchable Dimmable LED IP65 Fire SY9004WH Rated Downlight White

ADDITIONAL BEZELS


Chrome Bezel SY9006CC
Brushed Nickel Bezel SY9005BN
Matt Black Bezel SY9005BL
Gold Bezel SY9005G

Power Converter Included

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)

Page 22/23



6\\

DIMMABLE IP65 FIRE

This ultra slim fitting is designed to allow loft insulation to be continuously run over the back of the fitting (IC Rated), and features a speed fit tool free loop in - loop out terminal.

The fitting comes complete with a white bezel, but other colour options are also available to purchase separate, listed below.


Available in either warm or natural white, It is also fully dimmable from most standard wall dimmers, and also includes the power converter. The light output is equivalent to a 50W GU10 halogen lamp, but due to the latest LED technology it uses 85% less energy, helping to save money and the environment.











TECHNICAL INFO

Power Supply 240V

Colour Appearance Warm or Natural White

Colour Temperature 3000K - 3500K or 4000K - 4500K

Wattage 6W
Beam Angle 40°
Total Lumens 600lm
IP Rating IP65
Colour Rendering Index >Ra 80

Finish White (Chrome, Brushed Nickel,

& Matt Black available to

purchase separate)

Cut Out Size 68mm - 70mm

PART CODE & DESCRIPTION

6W LED Downlight Warm White SY9057WW 6W LED Downlight Natural White SY9057NW


ADDITIONAL BEZELS


Matt Black BezelSY9051BKChrome BezelSY9051CCBrushed Nickel BezelSY9051BN

Power Converter Included

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming) Page 22/23







POP UP SOCKET WITH GLASS TOP, SPEAKER & QI WIRELESS CHARGING



CEA P P ROHS

This motorised socket is available in a stylish black finish with a black glass top. The unit is motorised, simply touch the lid and the unit will rise. It also features an anti trap safety feature which stops the unit from closing when it senses an object

The built in Bluetooth Speakers enable users to stream music from connected devices & a Qi Charger is built into the lid to charge Qi enabled devices (will only charge when the unit is in the closed position)

Silver model also available, please see page 90.

PART CODE & DESCRIPTION

Motorised Pop Up Socket with Speaker with Qi Charging & Black Glass Top

SY9019BK/SPEAKER



Finish Black With Black Glass Top


Speaker Bluetooth

Wireless Charging Qi
UK Sockets 2

USB Ports 1 x USB-C (3.0A) & 1 X USB-A (2.1A)

IP Rating IP44 (when closed)





POP UP SOCKET SILVER WITH SPEAKER & QI WIRELESS CHARGING





The unit is motorised, simply touch the lid and the unit will rise. It also features an anti trap safety feature which stops the unit from closing when it senses an object

This model features a built in Bluetooth speaker to stream music from connected devices, and a Qi Charger built into the new look slim-line lid to charge Qi enabled devices (will only charge when the unit is in the closed position).

PART CODE & DESCRIPTION

Motorised Pop Up Socket with Speaker with Qi Charging & Silver Top

SY8994A/SPEAKER



TECHNICAL INFO

Finish Silver


Speaker Bluetooth

Wireless Charging Qi

UK Sockets 2

USB Ports 1 x USB-C (3.0A) & 1 X USB-A (2.1A)

IP Rating IP44 (when closed)



BLACK POP UP SOCKET WITH BLACK GLASS TOP & QI WIRELESS CHARGING



This motorised socket is available in a stylish black finish with a black glass top. The unit is motorised, simply touch the lid and the unit will rise. It also features an anti-trap safety feature which stops the unit from closing when it senses an object

A Qi Charger is built into the lid to charge Qi enabled devices (will only charge when the unit is in the closed position).

PART CODE & DESCRIPTION

Motorised Pop Up Socket with Qi Charging & Black Glass Top

SY9019/BLACK

TECHNICAL INFO

Finish Black With Black Glass Top


Wireless Charging Qi

UK Sockets 3

USB Ports 1 x USB-C (3.0A) & 1 X USB-A (2.1A)

IP Rating IP44 (when closed)







WHITE POP UP SOCKET WITH WHITE GLASS TOP & QI WIRELESS CHARGING



This motorised socket is available in a stylish white finish with a white glass top. The unit is motorised, simply touch the lid and the unit will rise. It also features an anti trap safety feature which stops the unit from closing when it senses an object

A Qi Charger is built into the lid to charge Qi enabled devices (will only charge when the unit is in the closed position).

PART CODE & DESCRIPTION

Motorised Pop Up Socket with Qi Charging & White Glass Top

SY9019/WHITE

TECHNICAL INFO


Finish White with White Glass Top

Wireless Charging Qi
UK Sockets 3

USB Ports 1 x USB-C (3.0A) & 1 X USB-A (2.1A)

IP Rating IP44 (when closed)





MOTORISED

POP UP SOCKET SILVER & QI WIRELESS CHARGING



The unit is motorised, simply touch the lid and the unit will rise. It also features an anti trap safety feature which stops the unit from closing when it senses an object

This models feature a Qi Charger built into the new look slim-line lid to charge Qi enabled devices (will only charge when the unit is in the closed position).

PART CODE & DESCRIPTION


Motorised Pop Up Socket with Qi Charging & Silver Top

SY8994A

TECHNICAL INFO

Finish	Silver	
Wireless Charging	Qi	
UK Sockets	3	
USB Ports	1 x USB-C (3.0A) & 1 X USB-A (2.1A)	
IP Rating	IP44 (when closed)	
Cable Length	1.9m	
Cut Out Size	95mm	





POWERTECH PRO



FLUSH PULL UP MODULE WITH QI WIRELESS CHARGING









This new version of the powertech module pulls up to reveal 3 UK sockets and 2 USB ports. It also features Qi wireless charging when the module is in any position.

The super-slim top is nearly flush with the work surface making it blend in with the surrounding environment, and is available in either a sleek black glass top or a stainless steel effect top.

PART CODE & DESCRIPTION

Powertech Pro Pull Up Module with Qi Charging Black Top SY9058BL

Powertech Pro Pull Up Module with Qi Charging Stainless Steel Top SY9058SS


TECHNICAL INFO

Finish Black or Stainless Steel

Wireless Charging Qi
UK Sockets 3

USB Ports 1 x USB-C (3.0A) & 1 X USB-A (2.1A)

IP RatingIP20Cable Length2mCut Out Size95mm



POWERTECH SPEAKER

PULL UP MODULE WITH BLUETOOTH SPEAKER







This Powertech Module features a built in audio speaker, which enables users to stream music from connected devices, such as smartphones or tablets. The model also includes 3 X UK sockets and 2 X USB ports for charging, capable of charging 1000mA per socket. The power tech has a simple installation process and is ideal for saving space in a kitchen or office environment. The unit is available with silver or stainless steel effect top.

PART CODE & DESCRIPTION

Powertech Pull Up Socket with Speaker Stainless Steel Effect Top

SY7192ST/SPEAKER

Powertech Pull Up Socket with Speaker SY7192SPEAKER & Silver Top

TECHNICAL INFO

Finish Silver or Stainless Steel


UK Sockets 3

USB Ports 2 X USB-A (2.0A combined)

IP Rating IP20

Cable Length 1.5m


Cut Out Size 102mm



POWERTECH QI



PULL UP MODULE WITH QI WIRELESS CHARGING











This version of the Powertech module pulls up to reveal 3 UK sockets and 2 USB ports. It also features Qi wireless charging when the module is pushed down.

The module comes in a choice of black or silver finish.

PART CODE & DESCRIPTION

Powertech Pull Up Module with Qi Charging
Black Top SY8

SY8993BK

Powertech Pull Up Module with Qi Charging Silver Top

SY8993SL


TECHNICAL INFO

Finish Black or Silver

Wireless Charging Qi
UK Sockets 3

USB Ports 2 X USB-A (2.1A per port)

IP Rating IP44 (when closed)



POWERTECH



PULL UP MODULE





Our Powertech Module includes 3 X UK sockets and 2 X USB ports for charging, capable of charging 1000mA per socket. The Powertech has a simple installation process and is ideal for saving space in a kitchen or office environment. The unit is available with silver, black or stainless steel effect top.

PART CODE & DESCRIPTION

Powertech Pull Up Socket Stainless Steel Effect Top SY7192ST.ST

Powertech Pull Up Socket SY7192

& Silver Top

Powertech Pull Up Socket SY7192BK

& Black Top


TECHNICAL INFO

Finish Silver, Black or Stainless Steel Effect

UK Sockets 3

USB Ports 2 X USB-A (2.0A combined)

IP RatingIP20Cable Length1.5mCut Out Size102mm



EVOLINE PORT CUISINE

PULL UP MODULE



Port Cuisine, the vertically or horizontally retractable power strip with three UK sockets, is the perfect upgrade for kitchens of the highest standards. The high-quality aluminium housing can be raised and lowered, flush with the working surface, even while in use. The see-saw cover allows room for the cords. All the plugs are accessible – but not in the way. This model is available with silver top, or stainless steel, but various finishes and colour options are available for special order, please contact our sales team with your requirements.

PART CODE & DESCRIPTION

Evoline Port Cuisine Silver Top SY9737


Evoline Port Cuisine

Stainless Steel Top SY9737SS

TECHNICAL INFO

Finish Silver or Stainless Steel

UK Sockets 3
IP Rating IP20
Cable Length 2.5m
Cut Out Size 102mm



EVOLINE PORT CUISINE

PULL UP MODULE WITH USB PORTS





Evoline Port Cuisine with USB ports is a vertically or horizontally retractable power strip with three UK sockets. The high-quality aluminium housing can be raised and lowered, flush with the working surface, even while in use. The see-saw cover allows room for the cords. This model also includes 2 USB ports which offers charging ability of 1000mA per port. The USB ports are compatible with ipod™ ipad™ and other mobile phones, cameras and GPS. This model comes with a Stainless Steel top as standard.

PART CODE & DESCRIPTION

Evoline Port Cuisine with USB & Stainless Steel Top

SY7366


TECHNICAL INFO

Finish Stainless Steel

UK Sockets

USB Ports 1 x USB-C & 1 X USB-A (2.1A max)

IP RatingIP20Cable Length3mCut Out Size102mm



EVOLINE BACK FLIP



MODULE



Compact and flush fitting, the EVOline Backflip provides access to discreet power connectivity, wherever it may be needed. Installed into a worktop and/or above most drawers the EVOline Backflip turns effortlessly with the press of a finger to reveal 2 UK power sockets and a USB charging point.

PART CODE & DESCRIPTION

PART CODE & DESCRIPTION					
	Evoline Back Flip Black Steel	SY9736BS/C			
	Evoline Back Flip Black Glass	SY9736BK/C	W.A		
	Evoline Back Flip Brass Effect	SY9736BE/C			
	Evoline Back Flip Grey Ceramic	SY9736GC/C			
	Evoline Back Flip Stainless Steel	SY9736SS/C			
	Evoline Back Flip White Steel	SY9736WS/C			
	Evoline Back Flip White Glass	SY9736WH/C			


TECHNICAL INFO


Finish Shown Opposite

UK Sockets 2

USB Ports 1 x USB-C (USB-A still available to order)

Cut Out Size 88 x 215mm





WIRELESS HIDDEN CHARGER

FAST QI CHARGER





This hidden wireless charger is compatible with all Qi-Enabled devices such as smartphones or tablets, for easy charging. The charger features built in overvoltage, overheating and short-circuit protection. Complete with 1.5m cable and USB plug, and a snap in mechanism. The Qi charger is compatible with Qi-Enabled devices (please visit our website for a full list of Qi-enabled devices)

PART CODE & DESCRIPTION

Wireless Hidden Fast Charger

SY7962/2A

TECHNICAL INFO

Standard Qi V 1.2 compliant


No of Coil

Wireless Charging Distance < 4mm
Input Voltage DC 5 - 12V
Input Current 2.0A
Rated Output 2.0A

Power Loading Max 15W Max Wireless Charging Efficiency >75%

Operating Temperature 0 - 40°C Self-Power Consumption 0.5W

Cut Out Size 60mm



24V NOVA

HIGH DEFINITION MULTI POINT LED CABINET LIGHT



This collection of 24V Multi-Point LED cabinet lights offers a choice of cool, natural or warm white LED, with a variety of different style bodies to suit different applications or tastes. The LED offers a good quality light output, enabling them to be used as task lighting in a kitchen, as well as adding mood lighting to any application.

TECHNICAL INFO

Finish Brushed Nickel

Power Supply 24Vdc Cable Length 2m

Colour Appearance Warm, Natural or Cool White
Colour Temperature 3000K - 3500K, 4000K - 4500K or

6000K - 6500K

Wattage 1.8W IP Rating IP44

Colour Rendering Index WW - Ra 82, NW - Ra 85,

CW - Ra 87

Total Lumens WW - 251 lm NW - 206 lm

CW - 2681m

Beam Angle 65°



COMPATIBLE POWER CONVERTERS

15W 24Vdc LED Power Converter (1-6 lights) SY2400 20W 24Vdc LED Power Converter (1-6 lights) SY2409

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

2m (SY7183) or 5m (SY7183/5) Extension Cable




DESIGNER TRI-LIGHT

PART CODE & DESCRIPTION

24V HD Nova LED Designer Tri-Light Brushed Nickel/ Warm, Natural or Cool White

SY2405WW, NW or CW






TRI-LIGHT

PART CODE & DESCRIPTION

24V HD Nova LED Tri-Light Brushed Nickel/ Warm, Natural or Cool White

SY2418WW, NW or CW





DESIGNER RECTI-LIGHT


PART CODE & DESCRIPTION

24V HD Nova LED Designer Recti-Light

Brushed Nickel/

Warm, Natural or Cool White

SY2417WW, NW or CW





RECESSED

PART CODE & DESCRIPTION

24V HD Nova LED Recessed Light

Brushed Nickel/

 $\textbf{Warm, Natural or Cool White} \qquad \qquad \text{SY2401WW, NW or CW}$





RECESSED/SURFACE



PART CODE & DESCRIPTION

24V HD Nova LED Rec/Sur Light Brushed Nickel/

Warm, Natural or Cool White

SY2403WW, NW or CW



Spacer depth

24V ORION



HIGH DEFINITION DIFFUSED LED CABINET LIGHT



The 24V Orion features a diffused cover, so there are no visible LED points in the fitting, and also has a 120 degree beam angle which fills cabinets or work surfaces, eliminating dark spots. The 24V Orion is available in warm, natural or cool white, offering an option for any type of kitchen design.

TECHNICAL INFO

Finish Brushed Nickel

Power Supply 24Vdc Cable Length 2m

Colour Appearance Warm, Natural or Cool White
Colour Temperature 3000K - 3500K, 4000K - 4500K or


6000K - 6500K

Colour Rendering Index WW - Ra 85, NW - Ra 85 CW - Ra 86

Total Lumens WW - 224lm NW - 253lm

CW - 1981m

Beam Angle 120°



COMPATIBLE POWER CONVERTERS

15W 24Vdc LED Power Converter (1-6 lights)20W 24Vdc LED Power Converter (1-6 lights)SY2409

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111-114

2m (SY7183) or 5m (SY7183/5) Extension Cable




DESIGNER TRI-LIGHT

PART CODE & DESCRIPTION

24V HD Orion LED Designer Tri-Light Brushed Nickel/

Warm, Natural or Cool White

SY2421WW,NW or CW






TRI-LIGHT

PART CODE & DESCRIPTION

24V HD Orion LED Tri-Light Brushed Nickel/ Warm, Natural or Cool White

SY2423WW,NW or CW

SY2422WW,NW or CW






DESIGNER RECTI-LIGHT

PART CODE & DESCRIPTION

24V HD Orion LED Designer Recti-Light

Brushed Nickel/

Warm, Natural or Cool White






RECESSED

PART CODE & DESCRIPTION

24V HD Orion LED Recessed Brushed Nickel/

Warm, Natural or Cool White

SY2402WW,NW or CW





RECESSED/SURFACE

PART CODE & DESCRIPTION

24V HD Orion LED Recessed/Surface Brushed Nickel/

Warm, Natural or Cool White



Spacer depth

24V ORION



HIGH DEFINITION LED FLAT PANEL




The 24V Orion has been designed to offer a superior light output and has a diffused cover with no visible LED points. The fitting also has unique magnetic fixing and enhanced curved edges.

PART CODE & DESCRIPTION

24V HD Orion LED Flat Panel SY2407WW, NW or CW

COMPATIBLE POWER CONVERTERS

15W 24Vdc LED Power Converter (1-4 lights) SY2400 20W 24Vdc LED Power Converter (1-5 lights) SY2409



TECHNICAL INFO

Finish Brushed Nickel

Power Supply 24Vdc Cable Length 1.5m

Colour Appearance Warm, Natural or Cool White
Colour Temperature 3000K - 3500K, 4000K - 4500K or

6000K - 6500K

Wattage 3.5W IP Rating IP20

Colour Rendering Index WW - Ra 93 NW - Ra 96

CW - Ra 95

Total Lumens WW - 230lm NW - 234lm

CW - 248lm

Beam Angle 120°

COMPATIBLE ACCESSORIES

Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

2m (SY7183) or 5m (SY7183/5) Extension Cable

24V ORION



HIGH DEFINITION LED SUPER SLIM CABINET LIGHT



This diffused cabinet light is surface mounted and has a super slim design with a magnetic cover to conceal the installation fixings. This sleek brushed steel fitting is available in a choice of warm, natural or cool white.

PART CODE & DESCRIPTION


24V HD Orion LED Super Slim Cabinet Light

SY2414WW, NW or CW

COMPATIBLE POWER CONVERTERS

15W 24Vdc LED Power Converter (1-6 lights)

SY2400



TECHNICAL INFO

Finish Brushed Nickel

Power Supply 24Vdc Cable Length 1.5m

Colour AppearanceWarm, Natural or Cool WhiteColour Temperature3000K - 3500K, 4000K - 4500K or

6000K - 6500K

Wattage 2W IP Rating IP20

Colour Rendering Index WW - Ra 81, NW - Ra 86,

CW - Ra 88

Total Lumens WW - 123lm, NW - 155lm,

CW - 150lm

Beam Angle 120°

COMPATIBLE ACCESSORIES


Kinetic Wireless Switching (inc. dimming)Page 22/23Wi-Fi 4 Zone ControlsPage 24/25Sensors, Switches & DimmersPage 111 - 114

2m (SY7183) or 5m (SY7183/5) Extension Cable

24V SUPERIOR COB



FLEXIBLE 5m REEL



This new 24V high output COB LED strip features LED points within close proximity to each other, creating a uniform light output with no spotting, perfect for illuminating handle-less kitchen designs. The strip has a depth of only 1.7mm so is ideal for situating underneath a worktop, and is suitable for installation on all coloured handle-less profiles without the need for an aluminium extrusion. This LED strip also comes with VHB **(Very High Bond)** tape.

PART CODE & DESCRIPTION

24V Superior COB LED 5m Reel SY2410WW, NW or CW

Accessories

1.5m Re-Connection Cable SY9002

TECHNICAL INFO

Power Supply 24Vdc Adhesive VHB

Cable Length 2m at both ends

Colour Appearance Warm, Natural or Cool White
Colour Temperature 3000K - 3500K, 4000K - 4500K or

6000K - 6500K


Wattage 4W/m IP Rating IP20

Cut Marks Every 50mm

LEDs per metre 420

COMPATIBLE POWER CONVERTERS

15W 24dc LED Power Converter (max 3m) SY2400 20W 24Vdc LED Power Converter (max 5m) SY2409




COMPATIBLE ACCESSORIES

Aluminium Extrusions Page 64
Kinetic Wireless Switching (inc. dimming) Page 22/23
Wi-Fi 4 Zone Controls Page 24/25
Sensors, Switches & Dimmers Page 111-114
2m (SY7183) or 5m (SY7183/5) Extension Cable

24V LED STRIP



FLEXIBLE 5m REEL



This 24V 5m reel is available in either warm, natural or cool white, offering an option for any kitchen design. The strip features 120 LED's per metre for a superb light output, ideal for using under a cabinet to light up a worktop. This LED strip also comes with VHB **(Very High Bond)** tape. A selection of extrusions are available to house the strip in, please refer to page 64. Mounting LED strip within an extrusion not only helps to keep runs straight and neat, it also assists with heat dissipation, therefore prolonging the life of the LED strip. A diffuser finishes off the clean look, and provides protection from dust and water splashes.

PART CODE & DESCRIPTION

24V LED Strip 5m Reel

SY2411WW, NW or CW

TECHNICAL INFO

Power Supply 24Vdc Adhesive VHB

Cable Length 2m at both ends

Colour Appearance Warm, Natural or Cool White
Colour Temperature 3000K - 3500K, 4000K - 4500K or

6000K - 6500K

Wattage 4W/m


IP Rating IP20

Cut Marks Every 50mm

LEDs per metre 120

COMPATIBLE POWER CONVERTERS

15W 24dc LED Power Converter (max 3m) SY2400 20W 24Vdc LED Power Converter (max 5m) SY2409



COMPATIBLE ACCESSORIES

Aluminium Extrusions Page 64
Kinetic Wireless Switching (inc. dimming) Page 22/23
Wi-Fi 4 Zone Controls Page 24/25
Sensors, Switches & Dimmers Page 111 - 114
2m (SY7183) or 5m (SY7183/5) Extension Cable

24V LED STRIP



IP65 FLEXIBLE LED STRIP



This 24V LED Strip is available in either warm, natural or cool white, offering an option for any kitchen design. The strip features 120 LED's per metre for a superb light output, ideal for using under a cabinet to light up a worktop, and is provided with VHB **(Very High Bond)** tape. A selection of Extrusions are available to house the strip in if required, please refer to page 64.

PART CODE & DESCRIPTION

500mm - 24V LED Flexible Strip

1M - 24V LED Flexible Strip

2M - 24V LED Flexible Strip

3M - 24V LED Flexible Strip

SY2413WW, NW or CW

SY2413WW, NW or CW

SY2424WW, NW or CW

COMPATIBLE POWER CONVERTERS

15W 24dc LED Power Converter (max 3m) SY2400 20W 24Vdc LED Power Converter (max 5m) SY2409

TECHNICAL INFO

Power Supply 24Vdc Adhesive VHB

Cable Length 2m at one end

Colour Appearance Warm, Natural or Cool White
Colour Temperature 3000K - 3500K, 4000K - 4500K or

6000K - 6500K 4W/m

Cut Marks Every 50mm

LEDs per metre 120





COMPATIBLE ACCESSORIES

Aluminium Extrusions Page 64
Kinetic Wireless Switching (inc. dimming) Page 22/23
Wi-Fi 4 Zone Controls Page 24/25
Sensors, Switches & Dimmers Page 111 - 114

2m (SY7183) or 5m (SY7183/5) Extension Cable

MICRO PIR SENSOR



PART CODE & DESCRIPTION

Mini Passive Infra Red Sensor
12 Way Distribution Block (a)

SY8815
SY7637

This sensor switch offers a discreet surface mounted or recessed solution for automatic switching of 12/24Vdc LED lighting. Connection via the Sycamore plug and play connector system allows connected lights to be turned on when it senses movement within a 3 metre distance at a 120 degree beam angle. The built-in timer can be adjusted from 30 to 150 seconds.

Unit includes connection for one light, a 12 Way Distribution Block can be purchased separately if required.

TECHNICAL INFO

Finish White Power Supply 12/24Vdc

Cable Length Sensor Cable - 2m, Input Cable - 1m

Output Cable - 1m

Max Current 10A Sensor Distance 1 - 3m Sensor Range 120°

Adjustable Timer 30 - 150 seconds

Wattage 12Vdc 100W

24Vdc 200W

IP Rating IP20

Mounting Recessed or Surface

(Vertical or Horizontal)

Guarantee 12 Months


MICRO DOOR/SWIPE SENSOR



PART CODE & DESCRIPTION

Mini Door/Swipe Sensor 12 Way Distribution Block (a) SY8814

000000



CELK TOHS

This sensor switch offers a discreet surface mounted or recessed solution for automatic switching of 12/24Vdc LED lighting.

This dual purpose sensor can be used as a door sensor, or a swipe sensor by choosing your desired mode using the simple switch on the side of the sensor.

When in swipe mode, the sensor will turn connected lights on and off when a hand is swiped in front of the sensor. When in door sensor mode, the sensor will turn connected lights on or off when a door is opened and closed.

Unit includes connection for one light, a 12 Way Distribution Block can be purchased separately if required.

TECHNICAL INFO

Finish White
Power Supply 12/24Vdc

Cable Length Sensor Cable - 2m, Input Cable - 1m

Output Cable - 1m

Max Current 10A Sensor Distance 1 - 3m

Sensor Range up to 70mm

Wattage 12Vdc 100W 24Vdc 200W

24 Vac 2

IP Rating IP20

Mounting Recessed or Surface

(Vertical or Horizontal)

Guarantee 12 Months

DOOR/SWIPE SENSOR



PART CODE & DESCRIPTION

Door/Swipe Sensor

SY7510C/SII

This innovative sensor can be used as either a door sensor, to automatically switch on lights on or off within cupboards or cabinets when the doors are opened and closed, or can be used as a swipe on/off sensor.

This sensor is small and discreet and comes in a silver finish. The sensor is suitable for use with all our 12/24Vdc LED lights and can be recessed or surface mounted.

TECHNICAL INFO

Finish Silver


Power Supply 12Vdc/24Vdc Cable Length 600mm

Wattage 15W (12Vdc) 30W (24Vdc)

IP Rating IP20

Mounting Recessed or Surface





CEK®₽₽®® Rohs

SIRIUS SLIMLINE DOOR SENSOR



PART CODE & DESCRIPTION

(a) Slimline Single Door Sensor(b) Slimline Double Door Sensor

SY8929E

12 Way Distribution Block (a) SY




CEUK POHS


The soft start Sirius infra red door sensor switches are designed to work with either a single/double cabinet or cupboard door, by automatically turning a light on and off when a door is opened or closed. It is compatible with all of our 12Vdc LED lighting ranges, and offers a simple plug and play connection system.

The unit includes connection for one light, however for more than one light a 12 way block is available to purchase separately. Features a simple self adhesive fixing method.

TECHNICAL INFO

Finish Silver
Power Supply 12Vdc
Cable Length 800mm
Wattage 24W
IP Rating IP20
Mounting Surface





TOUCH DIMMER



Touch Dimmer 12 Way Distribution Block (a)



CENT ® ☐ FOHS

The touch dimmer is compatible with all of our 12/24Vdc LED lighting ranges. It offers a simple plug and play connection system, so lights can be controlled from a single switch. The unit incorporates a soft blue light to aid location in the dark, and a surface mounting fixing method via 2 screws, which are hidden by the clip on brushed nickel fascia plate.

Unit includes connection for one light, a 12 Way Distribution Block can be purchased separately if required.

TECHNICAL INFO


Finish Silver


12Vdc/24Vdc **Power Supply**

Cable Length 2m

Wattage 60W (12Vdc) 120W (24Vdc)

IP Rating IP20 Mounting Surface





PART CODE & DESCRIPTION

Touch On/Off Sensor




CEKO AF W K ROHS

Touching the sensor pad supplied switches the 240VAC supply to the lighting circuit. Featuring adjustable touch sensitivity, the unit can be set to suit customer requirements.

Operates 12V/24V/350mA circuits via a relevant power converter, and also operates 240V circuits. The length of the sensor lead included is 1.5m long. Please note that the incoming and outgoing 240V supply cables are not supplied with this unit.

TECHNICAL INFO

Power Supply 240V Wattage 500W Max IP Ratina IP20



PIR SENSOR ADJUSTABLE LUX/TIMER





PART CODE & DESCRIPTION

Motion Sensor with Adjustable Timer & Lux

(a) Silver Cover

(b) IP65 Cover



PIR SENSOR



PART CODE & DESCRIPTION

PIR Sensor 12 Way Distribution Block (a)






off by detecting movement. This sensor can be used for LED, halogen and fluorescent light sources. The unit also features an adjustable timer, which can be set from 30 seconds up to 30 minutes. The unit also has photocell adjustment, so you can adjust the lux level sensor by 10 - 2000 lux. This enables the user to determine the lighting level at which the switch operates, for example, it can be set so the lights don't trigger in the daylight. TECHNICAL INFO

This motion sensor is suitable for installation in plinths or ceilings. It can be used to automatically switch lights on and

Finish White (Silver cover available to purchase separate) 240V **Power Supply** Sensor Distance Seated 4m Sensor Distance Walking Across 10m Sensor Distance Walking Towards 6m Sensor Range 360° Adjustable Timer 30 seconds - 30 minutes 10 - 2000 Lux Lux Adjustment Cut Out Size 34mm




This discreet passive infra red (PIR) motion detector can be recessed within wardrobes, cabinets, pantries and plinths. Easily installed using the Sycamore plug and play system, and compatible with Sycamore's 12/24Vdc LED lighting range.

The unit can sense movement up to 3m, and at a 110° angle. If the unit senses no movement after 30 seconds it will switch the lights off automatically.

Unit includes connection for one light, a 12 Way Distribution Block can be purchased separately if required.

TECHNICAL INFO

Finish Silver **Power Supply** 12Vdc/24Vdc Cable Length 2m Wattage 30W Max IP Rating IP20 Mounting Recessed Cut Out Size 16mm



LED LAMPS

GU10 COB STYLE



PART CODE & DESCRIPTION

COB Style 5W GU10 LED Lamp Warm, Natural or Cool White

SY7534B/WW, NW or CW

Our 5W LED lamp features the very latest in COB style technology. It is an ideal alternative to GU10 halogen lamps, and is available in warm, natural or cool white.

TECHNICAL INFO

Power Supply 240V

Colour Appearance Warm, Natural or Cool White


Colour Temperature 3000K, 4000K or 6000K

Wattage 5W Beam Angle 36°

Total Lumens WW - 593lm NW - 680lm,

CW - 635lm

Colour Rendering Index >Ra 80



LED LAMPS FOR PENDANTS









E27 Filament LED Lamps 5W Dimmable

Part Number	Lamp Type	Wattage	Colour Temperature
CR7239	E27 Round	5W	Warm White 2700K
SY7986/E27GLS	E27 GLS	5W	Warm White 2700K
SY7986/E27	E27 Candle	5W	Warm White 2700K







E14 Filament LED Lamps 5W Dimmable

Part Number	Lamp Type	Wattage	Colour Temperature
CR7246	E14 Round	5W	Warm White 2700K
SY7618A/2700	E14 Candle	5W	Warm White 2700K





E27 Candle LED Lamps Dimmable

Part Number	Lamp Type	Wattage	Colour Temperature
CR9226	E27 Candle	5.5W	Warm White 2700K
CR13513	E27 Candle	5W	Natural White 4000K
CR9288	E27 Candle	5.5W	Cool White 6500K





E14 Candle LED Lamps Dimmable

Part Number	Lamp Type	Wattage	Colour Temperature
CR13490	E14 Candle	5W	Warm White 2700K
CR13520	E14 Candle	5W	Natural White 4000K
SY7618A/6000K	E14 Candle	6W	Cool White 6000K





G9 LED Lamps

Part Number	Lamp Type	Wattage	Colour Temperature
CR3415	G9	2.5W	Warm White 2700K
CR3422	G9	2.5W	Natural White 4000K

KINETIC LED POWER CONVERTERS



This unit combines the Kinetic receiver with a dimmable driver for low loads of 15W or 20W or less. This driver can be used with the wall plate switches on page 23, or with the Smart App & voice control via Alexa or Google home.

Compatible with all of Sycamore's 12Vdc LED lighting.

PART CODE & DESCRIPTION

15W Dimmable Power Converter with Built in Kinetic Receiver

20W Dimmable Power Converter with

Built in Kinetic Receiver

SY8996

SY8999

EMC SELV F W C C

Download the Smart Life app here:

IOS

ANDROID






TECHNICAL INFO

Power Supply

Wattage

12Vdc

15W or 20W



DIMMABLE LED POWER CONVERTERS



This dimmable power converter enables users to dim 12Vdc LED lighting via a rotary wall dimmer. It features a fast fit plug in system, which allows connection of compatible lights into a pre-wired distribution block on the 12V side of the unit. If you require a higher wattage dimmable power converter please contact our technical team for advice at tech@sycamoreLED.com.

PART CODE & DESCRIPTION

30W Dimmable Power Converter

SY7443A/MF

50W Dimmable Power Converter

SY7445B/50W

EMC SELV F W C C C


TECHNICAL INFO


Power Supply

Wattage

12Vdc

30W or 50W






12VDC LED POWER CONVERTERS




All the Sycamore 12Vdc LED Power supplies feature a fast fit plug in system, which allows connection of compatible lights into a prewired distribution block on the 12V side of the unit.

PART CODE & DESCRIPTION 8W 12Vdc LED Power Converter (3 port) SY9980B 20mm



















GLOSSARY OF ICONS AND TECHNICAL DATA

\in	Indicates the compliance with the low voltage and electromagnetic compatibly
UK	Indicates the compliance with the applicable requirements from products sold within the UK.
	Class I lighting: includes earth protection as a complementary security measure against electrical shocks
	Class II lighting: includes a reinforced or double insulation as a protection against electrical shocks
	Class III lighting: the protection against electrical shocks comes from the supply of very low voltage tension
F	Suitable for installation on normally combustible surfaces
M	Suitable for use in furniture
	For indoor use only
	WEEE Compliant
ROHS	ROHS compliant
5	Our products carry a 5-year warranty. This excludes battery operated products, accessories, pendant lighting and power ports. Please refer to our website for further information on our terms and conditions
KINETIC CLAMPONIAL FEMALES FEMALES	Compatible with our 12/24V Kinetic Smart Lighting control system. Please see pages 22 & 23 for more information.
	Compatible with our 240V Kinetic Smart Lighting control system. Please see pages 22 & 23 for more information.
TUNABLE	This product can be changed from warm/natural/cool white LED using a remote control or smart device.
SWITCHABLE	This product can be changed from warm/natural/cool white LED and dimmed using a built-in switch.
- <u>- </u>	This product can be changed from warm/natural/cool white LED and using a built-in switch. Not dimmable.
÷ Ú É RGB	This product can be changed to many different colours and dimmed using a remote control or smart device.
O _o o	The pop up socket is motorised - simply touch the botton on the lid and the unit will rise. Touch again to lower.
**	The product features a built-in Bluetooth Speaker to stream music from connected devices.
\$\Psi\$ USB	The product features USB ports for charging purposes. Please see individual specification for further details.
Qi charging	This product features a built-in Qi Charger for charging compatible Qi enabled devices.
K	This product will switch on when it senses movement within a specific range, and switch off once no further motion is detected.
((4)))	The product will switch on once a hand is swiped within a specified distance from the sensor. Swipe again to turn off.
	The product will switch on once a door is opened. Closing the door will switch the product off.
	The product will switch on when physically touched. Touch again to turn off.
(((3)))	The product will switch on when the drawer is opened, Close drawer

Colour Appearance and Colour Temperature

The most common terminology is to classify colour temperature as one of three options. These being warm white (approx 3000k), natural white (approx 4000k) and cool white (approx 6000k).

Colour Rendering Index (CRI)

This is a figure that indicates the accuracy of the reflective surface colour of an object when subjected to artificial light. For example an object in daylight on a reasonably sunny day will be subject to a CRI of 100 from the light source, which in this case would be daylight, the sun. Theoretically the colour of an object will be 100% true.

Once the same object is placed into a dark room and a light fitting with a CRI of 85 is illuminating it, then the colour of that object will be 85% of its true colour. Therefore the higher the CRI, the more accurate the colour.

Colour temperature has a bearing on this as a white object would appear "yellow" if illuminated by a warm white light source. Careful consideration has to be taken to ensure that the correct type of light with the correct CRI and colour temperature is selected for any given installation.

A CRI of 80 is the minimum standard.

Total Lumens

This relates to the amount of light (lumens) emitted from a light fitting in relation to the amount of power it uses to create this output. There are now regulations in place that state minimum lumens per watt criteria and any lights that do not conform aren't able to be used in certain applications. Advice should always be taken to ensure that the correct lighting is used on any installation.

Beam Angles


The beam angle of a light fitting allows the installer to determine the spacing of light fittings as to achieve the most uniform, consistent lighting onto the desired area.

ERP Directive

ERP Directive effective from 5th December 2019, commission regulation (EU) No 2019/2020 laid down new eco-design requirements for light sources and separate control gears.

Furthermore, the energy labelling was newly regulated and simplified in scope and was introduced for light sources from 1st September 2021.

A typical ERP label is shown.



EnabLED

LEDs and LED controls are the future of lighting, and as LED capabilities continue to evolve and expand, new markets are opening up all the time. Developing new, innovative solutions for tomorrow's new LED applications takes significant investment in research and design, so by joining the EnabLED licensing program, Sycamore LED has gained access to over 490 Signify inventions and patented technologies, which we can now build into our own products. With access to these cutting-edge technologies, we can gain greater freedom to design optimal solutions for our products. We can shorten our time to market and also achieve an excellent balance of cost-to-quality including cost-effectiveness in our component sourcing.

Please visit www.signify.com/enabled to confirm which companies are currently licensed in the scheme and what the EnabLED licensing program covers in more detail.



to switch off.

TERMS & CONDITIONS

- 1. DEFINITIONS: a) The ''seller'' means Sycamore Lighting Ltd. b) The "buyer" means the person who buys or agrees to buy the goods from the seller. c) The 'goods' means all items which the buyer agrees to buy from the seller.
- 2. GENERAL: Orders are only accepted subject to the Conditions of Sale set out below and the seller shall not be bound by any other terms, written, verbal or implied, or which are conditions customary in the trade and whether contained in customer's order or not. These conditions shall apply unless expressly varied by the seller in writing.
- 3. TERMS: Credit accounts are nett strictly within 30 days. Interest at a rate of 3% per annum above NatWest base rate, together with any expenses incurred in collecting payments, will be added to the agreed price in respect of any part thereof not paid, on or before the due date. Where a new account is to be opened two trade references are required. The seller has the right to discontinue delivery without notice if the buyer defaults in payment, or if circumstances warrant such discontinuance. The seller also has the right to refuse credit terms to a buyer for any reason. Pro-forma orders will only be delivered when the seller has received payment in full, including confirmed clearance of any cheque.
- 4. PRICES: Whilst every endeavour will be made to deliver at the prices quoted, the seller reserves the right to invoice at the price ruling at the date of delivery. All prices are subject to VAT at the rate prevailing at the date of invoice.
- 5. RISK AND DELIVERY: a) Goods are delivered to the buyer when the seller makes them available to the buyer (or any agent of the buyer) at the sellers premises or other delivery point agreed by the seller and risk in the goods passes when they are delivered to the buyer. b) The seller shall not be liable for any penalty, loss, injury, damage or failure in delivery from any cause at all nor shall any such delay or failure entitle for any buyer to refuse to accept any delivery or to repudiate the contract. c) Any dates quoted by the seller for delivery of the goods are approximate only and shall not form part of the contract and the buyer acknowledges that in the performance expected of the seller no regard has been paid to any quoted delivery dates.
- 6. CARRIAGE AND ADMINISTRATION CHARGES: An administration charge of £5.00 will be added to all orders under £30.00. A carriage charge of £8.50 will be added to all invoices on orders of under £150.00 excluding VAT to UK mainland addresses. All offshore islands and EC countries will incur a separate delivery charge, based on the weight of the total order. Please note administration and delivery charges are subject to change without prior notice.
- 7. CLAIMS: Claims must be notified in writing within seven days of receipt, otherwise responsibility cannot be accepted. The seller's liability shall be limited to, at the seller's option, replacing the goods or refunding the price of the goods. Under no circumstances shall the liability of the seller exceed the price of the goods. Replacements for damaged goods will be charged and credit issued on the return of the damaged goods to the seller in the original packaging.

- 8. RETENTION OF TITLE: a) In spite of delivery having been made, property in the goods shall not pass from the seller until payment in full of the price by the buyer. B) Not withstanding delivery, property in the goods shall not pass from the seller until all other sums owed by the buyer to the seller have been paid in full. c) Until payment in full for the goods, the buyer shall hold the goods on a fiduciary basis as a bailee for the seller. d) Whilst the buyer has the right to dispose of the goods in the ordinary course of business on a bona fide sale without notice to the customer of the seller's rights hereunder, the entire proceeds of sale or otherwise of the goods shall be held in trust for the seller until payment in full for the goods. e) Until payment in full for the goods the buyer hereby grants the seller the right to enter any premises where the goods are stored in order to re-possess or inspect them.
- 9. BREACH AND INSOLVENCY: If the buyer breaches any condition of this contract or becomes subject to an Administration Order or becomes bankrupt or has a receiver appointed for or distress is levied on any part of its assets or business or goes into liquidation or makes any composition with its creditors, the seller shall be entitled (whether in respect of this contract or any other) to: a) Withhold any further deliveries to the buyer and/or cancel the contract without liability; b) Appropriate any payment made by the buyer to such of the goods (whether supplied under this contract or any other) as the seller shall think fit; c) Immediate payment of all sums whatever, owing by the buyer to the seller notwithstanding any previous agreement to the contrary; d) Exercise any of its right pursuant to clause 8 above.
- 10. PRODUCT INFORMATION: Although the seller shall use its best endeavours to ensure that the information contained in the seller's catalogue is correct at the time of going to press, the seller shall not be under any liability for any damage, loss or expense resulting from any error or omission contained in the seller's catalogue. Goods supplied may vary in detail from the illustrations, drawings and descriptions (which are approximate and for guidance only) in the seller's catalogue as a result of improvements or modifications. Colour finishes will be maintained as accurately as possible, but matching cannot be guaranteed.
- 11. FORCE MAJEURE: The seller shall not be liable for any default due to any act of God, war, strikes, lock-outs or other industrial action, difficulties in obtaining labour or parts, government or other restrictions or regulations or other event beyond the reasonable control of the seller.
- 12. LAW AND JURISDICTION: All disputes arising out of or in connection with the contract shall be governed by English law and the buyer accepts the jurisdiction of the Courts Of England.
- 13. RETURN AND RESTOCKING: When goods are agreed for a return or cancellation the buyer shall pay a handling or restocking charge to cover administration and inspection charges involved in reprocessing products back into stock. The charge will be subject to change without prior notice but is currently 25% of the invoiced value of the goods. Non standard and special items ordered by the buyer cannot be accepted for return.
- 14. GUARANTEES: Terms and conditions apply to the guarantees, and lamp life of our products. Please refer to our website for further details.
- 15. CUT OUT SIZES AND DIMENSIONS: These are correct at time of printing. We do not recommend any holes are cut until goods are received and checked.



Order by phone: 0113 286 6686

Order by email: sales@sycamoreled.com

Order online: www.sycamoreled.com *account holders only, apply online.





SycamoreLED.com

Unit 6 Astley Lane Industrial Estate Swillington Leeds West Yorkshire LS26 8XT

www.sycamoreLED.com



